

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>		5. LEASE DESIGNATION AND SERIAL NO. NM 0175779
2. NAME OF OPERATOR Trans Rella Oil & Co. Synco Oil Corporation		6. IF INDIAN, ALLOTTEE OR TRIBE NAME
3. ADDRESS OF OPERATOR 7890 E. Prentice Ave. Englewood, Colorado 80110		7. UNIT AGREEMENT NAME
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1850' FSL & 790' FEL		8. FARM OR LEASE NAME Hanson
14. PERMIT NO.		9. WELL NO. #1
15. ELEVATIONS (Show whether Dr. or CR, etc.)		10. FIELD AND POOL, OR WILDCAT South Blanco, PC
		11. SEC., T., R., M., OR BLE. AND. SURVEY OR AREA Sec. 6, T23N, R1W
		12. COUNTY OR PARISH Rio Arriba
		13. STATE NM

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

This well is presently producing at a non-commercial rate from casing perforations in the upper Pictured Cliffs interval 3366 to 3376'. We propose to squeeze cement perforations from 3366 to 3376 with an estimated 100 sacks. Deepen the well below the present depth of 3410 feet and penetrate the second Pictured Cliffs sand estimated from 3450 to 3470 feet with an estimated total depth of 3490 feet. Run a 2½" liner from total depth to 3300 feet. Fracture treat the lower Pictured Cliffs. Run 1" tubing to 3450 feet. Test and complete.

We plan no surface disturbance

18. I hereby certify that the foregoing is true and correct
ORIGINAL SIGNED BY
E. L. FUNDINGSLAND, JR.

SIGNED

TITLE

Vice President

DATE

5-9-75

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side