



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Budget Bureau No. 42-R358.
Approval expires 12-31-60.

Land Office W-317677
Lease No. _____
Unit _____

SUNDRY NOTICES AND REPORTS ON WELLS

RECEIVED

NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	X	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL			

OCT 30 1961

U. S. GEOLOGICAL SURVEY
FARMINGTON, NEW MEXICO

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Well No. W-317677 is located 120 ft. from N line and 120 ft. from E line of sec. 1
_____ 19____
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Undershot (Field) _____ (County or Subdivision) _____ (State or Territory)

The elevation of the derrick floor above sea level is _____ ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Well Record:
1. 7" casing to 110' and 2 1/2" hole from 110' to 1700' with sand. Tap with 2 1/2" seal 110' to 1150'.
2. Cement 7" casing around shoe with sufficient cement to bring cement to 1700' (see record 1170').

NOV 2 1961
OIL CON. COM.
DIST. 3

Proposed program: 1. Add 7" casing to 110' and 2 1/2" hole from 110' to 1700' with sand. Tap with 2 1/2" seal 110' to 1150'.
2. Cement 7" casing around shoe with sufficient cement to bring cement to 1700' (see record 1170').

S. J. JACOBY, Jr., Engineer

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Leam and Relations
Address P. O. Box 151
Uranium, Colorado

By Clinton White
Agent
Title _____

3. After cement sets shoot zone $\frac{1}{2}$ " holes at 1000' and break circulation between 5-5/8" & 7" annulus with mud.
4. While circulating mud pull 5-5/8" casing and jack out 10-3/4" casing.
5. After pulling 10-3/4" and 5-5/8" casing, string cement 7" casing, stage No. 2 through shot holes at 1000' with sufficient cement to fill to 440' (top of mesa verde).
6. Run out plug below 7" casing to 3400' and crack-jet 3400-4400' open hole.
7. Fill frac pay zone 3100' to 3200'.
8. Decision to depend upon test tests on the frac job.