

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

334735

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Florence F

9. WELL NO.

233Y

10. FIELD AND POOL, OR WILDCAT

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

23, 1

12. COUNTY OR PARISH 13. STATE

10 Arrica New Mex.

1. OIL ☐ WELL GAS ☒ WELL OTHER ☐

2. NAME OF OPERATOR

D. L. Florence

3. ADDRESS OF OPERATOR

5420 Villa View Dr. Farmington, New Mexico

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

1050' / SE, 1050' / SE

14. PERMIT NO.

15. ELEVATIONS (Show whether DE, RT, GR, etc.)

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREAT

MULTIPLE COMPLETE

FRACTURE TREATMENT

ALTERING CASING

SHOOT OR ACIDIZE

ABANDON*

SHOOTING OR ACIDIZING

ABANDONMENT*

REPAIR WELL

CHANGE PLANS

(Other)

(Note: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Called for verbal approval 11-4-76

(1) Loaded 2 7/8" casing with water filling well. Spotted 5sk. cement plug inside 2 7/8" via 1" tubing 3325'-3175'. Pulled and layed down tubing.


(2) Cut off surface casing and plate. Pulled strain on 2 7/8" casing and backed off at 270'. Laid down 2 7/8" casing.

(3) Ran 1 1/2" tubing to 320', spotted 20 sk. cement plug 320'-220'.

(4) Pulled tubing to 110', spotted 17sk. cement plug 110'-60'.

(5) Pulled tubing to 30', spotted 10sk. cement spur 30'-0'.

(6) Erected hole marker.



18. I hereby certify that the foregoing is true and correct.

SIGNED

TITLE

DATE

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

NM OCC

*See Instructions on Reverse Side

APPROVED

DEC 18 1980
James F. Sims
JAMES F. SIMS
DISTRICT OIL & GAS SUPERVISOR