U.S.G.S. — 1 OCC Aztec

Form 9-331
(May 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE* (Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.: SF-078272

6. IF INDIAN, ALLOTTEE OR TRIBE NAME:

7. UNIT AGREEMENT NAME:

8. FARM OR LEASE NAME: Dunn

9. WELL NO.: 8

10. FIELD AND POOL, OR WILDCAT: Lybrook Gallup

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA: Sec. 9 T23N R7W

12. COUNTY OR PARISH: Rio Arriba

13. STATE: N. M.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL [X] GAS WELL [ ] OTHER

2. NAME OF OPERATOR: BCO, Inc.

3. ADDRESS OF OPERATOR: 135 Grant Ave. Santa Fe, New Mexico 87501

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface: 1980' FNL 600' FWL Sec. 9 T23N R7W

14. PERMIT NO.:

15. ELEVATIONS (Show whether DF, RT, GR, etc.): GR 7191

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:				SUBSEQUENT REPORT OF:			
TEST WATER SHUT-OFF	[ ]	PULL OR ALTER CASING	[ ]	WATER SHUT-OFF	[ ]	REPAIRING WELL	[ ]
FRACTURE TREAT	[ ]	MULTIPLE COMPLETE	[ ]	FRACTURE TREATMENT	[ ]	ALTERING CASING	[ ]
SHOOT OR ACIDIZE	[ ]	ABANDON*	[ ]	SHOOTING OR ACIDIZING	[ ]	ABANDONMENT*	[ ]
REPAIR WELL	[ ]	CHANGE PLANS	[ ]	(Other) Drilling Progress			XX
(Other)				(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)			

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

7-16-81 Notified Rosabel with U. S. G. S. answering service we intend to cement surface pipe on this well between 12:00 and 3:00 P.M.

7-16-81 Drilled 12 1/4" hole and ran 201' 23 # 8 5/8 ERW surface pipe. Landed pipe at 212'. Cemented with 150 sacks Class B 3% CaCl cement, with 1/4 # flocell per sack. Circulated 7 barrels cement. Plug down 3:45 P.M.

7-17-81 Drilled out surface at 12:01 A.M. Depth at 6:00 A.M. was 1137.

RECEIVED JUL 23 1981 OIL CON. COM. DIST. 3

JUL 23 1981 FARMINGTON BY Ellen

18. I hereby certify that the foregoing is true and correct

SIGNED Harry R. Boyle TITLE President DATE July 17, 1981

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

NMOCC