

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☒ other

2. NAME OF OPERATOR  
CHACE OIL COMPANY, INC.

3. ADDRESS OF OPERATOR  
313 Washington SE Albuquerque, NM 87108

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) Unit "I" 1850' FSL and 790' FEL  
AT SURFACE:  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:  
TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) Spud Well

SUBSEQUENT REPORT OF:

☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐

RECEIVED  
NOV 06 1981  
U. S. GEOLOGICAL SURVEY  
FARMINGTON, N. M.

5. LEASE  
Contract #47  
6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
Jicarilla  
7. UNIT AGREEMENT NAME  
8. FARM OR LEASE NAME  
Jicarilla Tribal Contract #47  
9. WELL NO.  
#1 - ~~18144~~  
10. FIELD OR WILDCAT NAME Chaco Dakota Exp.  
Ballard Pictured Cliffs  
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
I Sec. 12, T23N, R4W  
12. COUNTY OR PARISH Rio Arriba  
13. STATE New Mexico  
14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
7384' CB

RECEIVED  
DEC 7 1981  
OIL CON. COM.  
DIST. 3

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Operations to commence approximately December 1, 1981. 4½" casing to be run to 7760'. Cemented in 2 stages. 7700' float collar. First stage - 750 sxs 50-50 posmix; second stage - 550 sxs 40/60 posmix, 12% gel and 200 sxs Class "B" cement.

Will log with induction and density logs. No cores. No hazards expected.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature] TITLE Geologist DATE 10/27/81

(This space for Federal or State office use)  
RAYMOND W. VINYARD

APPROVED BY \_\_\_\_\_ TITLE AGING DISTRICT SUPERVISOR DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY: