6. IF INDIAN, ALLOTTEE OR TRIBE NAME

5. LEASE #362

UNITED STATES DEPARTMENT OF THE INTERIOR **GEOLOGICAL SURVEY**

	Jicarilla Apache
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME
Do not use this form for proposals to drill or to deepen or plug back to a difference reservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME
1. oil gas other Dual Completion	9. WELL NO.
	#9 Martin-Florance
2. NAME OF OPERATOR W. B. Martin & Associates	10. FIELD OR WILDCAT NAME
	S. Lindrith Gallup Dakota Ext.
3. ADDRESS OF OPERATOR 2110 N. Sullivan, Farmington, NM 87401	11. SEC., T., R., M., OR BLK. AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space	NE CE E
helow)	T23N R4W
AT SURFACE: 1980' FSL and 660' FEL	12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL:	Rio Arriba New Mexico
AT TOTAL DEPTH:	14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTIC	Ε,
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF	Gr.\ 7063'
TEST WATER SHUT-OFF	
FRACTURE TREAT	
SHOOT OR ACIDIZE	Č.
REPAIR WELL	(NOTE: Report results of many legislation of the control of the co
PULL OR ALTER CASING UM MULTIPLE COMPLETE UM MULTIPLE COMPLETE UM MULTIPLE COMPLETE UM MULTIPLE MULTIP	change on Form 9 B G E I V E
CHANGE ZONES	of the US
ABANDON*	** APR2 2 1983 •
(other) Cement Record	0000
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly sincluding estimated date of starting any proposed work. If well measured and true vertical depths for all markers and zones pertinued of the completed of the completed operations: Drilled 7 7	inent to this work.)*
low water loss mud. Ran open hole	logs. Ran 7308' of new 5 1/2" K-55
17 lbs/ft casing. Cemented as foll	.ows:
Equipment Depth Cement	05 .1) 50/50 D 49/0-1 4 11- V-1:4-
1. Float Collar 7270' 813ft 3(62	25 sks) 50/50 Poz 6% Gel 6 lbs Kolite 50 sks) 50/50 Poz 6% Gel 6 lbs Kolite
2. Stage Collar 7210' 325 ft (25	00 sks) 50/50 Poz 6% Gel 6 lbs Kolite
J. Stage Collar 5150 520tt (40	00 sks) 50/50 Poz 6% Gel 6 lbs Kolite 18ft (100 sks) Class B 2% CaCl
Idli III I	2
04/13/83 WOC	
Subsurface Safety Valve: Manu. and Type	Set @ Ft.
18. I hereby certify that the foregoing is true and correct	
SIGNED UB Martin & TITLE Operator Re	P. DATE April 14, 1983
(This space for Federal or State	
	DATE
APPROVED BY THE CONDITIONS OF APPROVAL, IF ANY:	Unit
	of contraction
	AGUEFIEU FOR RECORD

*See Instructions on Reverse Side

APR 2 0 1983