(November 1983) (Formerly 9–331)  DEPARTMENT OF THE INTERIOR (Other instructions on re- BUREAU OF LAND MANAGEMENT  SUNDRY NOTICES AND REPORTS ON WELLS  (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  Use "APPLICATION FOR PERMIT—" for such proposals.)			Budget Bureau No. 1004-0135 Expires August 31, 1985  5. LEASE DESIGNATION AND SERIAL NO.
			SF 078359
			6. IF INDIAN, ALLOTTEE OR TRIBE NAME
OIL XX GAS WELL OTHER			7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR			S. FARM OR LEASE NAME
Bannon Energy, Inc. c/o Holcomb Oil & Gas, Inc.			Federal 8
3. ADDRESS OF OPERATOR P.O. Box 2058, Farmington, NM 87499 4. Location of well (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface			9. WELL NO.
			1
			10. FIELD AND POOL, OR WILDCAT
Unit I 2173' FSL x	Counselors Gallup Dakota 11. SEC., T., B., M., OR BLE. AND SURVEY OR ARMA		
			Sec. 8 T23N R6W
14. PERMIT NO. 15. ELEVATIONS (Show whether DF, RT, GR, etc.)			12. COUNTY OR PARISH 13. STATE
API 30-039-24554	6864' (	GR	Rio Arriba NM
16. Check	Appropriate Box To Indicate N	Nature of Notice Pages	
Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data  NOTICE OF INTENTION TO:  SUBSEQUENT REPORT OF:			
TEST WATER BEST-ORE	on the state of th	_	To the state of th
FRACTURE PREAT	MULTIPLE COMPLETE	WATER SHUT-OFF	EEPAIRING WELL
	SUABANDON -	FRACTURE TREATMENT SHOOTING OR ACIDIZING	ALTERING CASING ABANDONMENT*
REPAIR WELL MAR 10 19	CHANGE PLANS	1	Cemnt Summary (AMENDED)
(Other) OIL CON	DIV.	Completion or Record	ts of multiple completion on Well pletion Report and Log form.)
17. DESCRIBE PROPOSED OR COMPLETED proposed work. If pulled different to this work.)	OPERATIONS (Clearly state all pertinen ectionally drilled, give subsurface local	t details and also neethers dots	s. including estimated date of starting any cal depths for all markers and zones perti-
AMENDED REPORT			
TD - 5650'. Ran 128 5648'. Float collar - follows:	joints, 4 1/2", 11.6 5613' (KB), Stage coll	o lb., J-55 casing. M ar - 3430' (KB). Fir	easured 5648', set at st stage cemented as
Flocheck-21, 10 bbls.	water, 10 bbls. CaCl <sup>2</sup> water spacer followed 100 sx. 50/50 poz (140 Plug down.	by 300 sacks, (5	46 cubic ft.) 65-35
Circulated cement by	stage collar. Circulate	ed 4 hours between st	ages.
cubic ft.) 65-35 p	pacer program as the formula, 12% gel, 6 l Class "B" cement and c	/4 lbs. Gilsonite pe	r sack followed by 50
			~)
		Co. A.	en de la companya de La companya de la co
		·	
18. I hereby certify that the foregoin	٨		
SIGNED W. J. Holcomb	comby TITLE AS	gent	<b>DATE</b> 1-31-90
(This space for Federal or State	office use)	Λ.	OCEDIED FOR DECORD
APPROVED BY	TITLE	A	CCEPTED FOR RECORD
CONDITIONS OF APPROVAL, I			MAR 1.4 (990
			作権的 加強 IOTU
	*C I	On Royena Side	Attenno Up neodonae ArteA

"See Instructions on Keverse Side

PARIMINOTORI RESOURCE MARA