Form 3160-5 (November 1994)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or reenter an abandoned well. Use Form 3160-3 (APD) for such approach

FORM APPROVED OMB No. 1004-0135 Expires July 31, 1996

Lease Serial No.

BIA #38

6. If Indian, Allottee or Tribe Name

abandoned well	Jicarilla Apache					
SUBMIT IN TRIPL	JCATE - Other instr	uctions quaevers	ie side	7. If Unit or CA/Agreement, Name and/or No.		
1. Type of Well						
χ Oil Well 🔲 Gas Well	Other			8. Well Name and No.		
2. Name of Operator				Otero #1		
Elm Ridge Resources, Inc.			9. API Well No. 30-039-26885			
3a. Address		3b. Phone No. (include area code) 505-632-3476				
PO Box 189, Farmington, NM 87499				10. Field and Pool, or Exploratory Area		
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)				Gallo Gallup Dakota		
910' FNL & 1850' FEL				11. County or Parish, State		
Sec. 5-T23N-R5W				11. County of Parisit, State		
				Rio Arriba, New Mexico		
12. CHECK APPROPRIATE BOX(E	S) TO INDICATE NATURE	OF NOTICE, REPORT	, OR OTHER DA	ГА		
TYPE OF SUBMISSION	TYPE OF ACTION					
X Notice of Intent	Acidize	Deepen	Production (S	tart/Resume) Water Shut-Off		
Subsequent Report	Alter Casing Casing Repair	Fracture Treat New Construction	Reclamation Recomplete	Well Integrity X Other Drilling		
Final Abandonment Notice	Change Plans Convert to Injection	Plug and Abandon Plug Back		Temporarily Abandon Water Disposal		
Attack the Bond under which the work Following completion of the involved ope	will be performed or provide the rations. If the operation results in ndonment Notices shall be filed or	Bond No. on file with BLM.	BIA. Required subse	sed work and approximate duration thereof depths of all pertinent markers and zones squent reports shall be filed within 30 days interval, a Form 3160-4 shall be filed once have been completed, and the operator has		
Spud well on 2-24-02. Drilled 1	2-1/4 hole to 365' KB. F	Ran 8-jts 8-5/8, 24# ,	J-55 STC casi	ng set @ 360.96' KB. Cemented		

Spud well on 2-24-02. Drilled 12-1/4 hole to 365' KB. Ran 8-jts 8-5/8, 24#, J-55 STC casing set @ 360.96' KB. Cemented with 300 sx Class "B", 2% CC. Displace 20 bbls water. Plug down @ 4:15 PM on 2-24-02. Circulate 20 bbls cement to surface. Drilled 7-7/8 to 5712' KB. TD reached @ 4:45 PM on 03-11-02. Ran 151-joints 4-1/2,N80, 11.6# LTC casing set @ 6732.11' KB. Stage tool set @ 4642'.KB. Cemented first stage w/685 sx 50/50 H POZ, 2% gel, 5# gilsonite, 1/4# Flocele, .5% HALAD-9. Bump plug w/1850 PSI and open stage tool. Circulate 4 hours and 10 bbls cement to surface. Cement 2nd stage w/875 sx 65/35 STD POZ, 6% gel, 1/4# flocele, 10# gilsonite, 1% CC and 50 sx H POZ, 1/4# flocele, .5% HALAD-9, .2% CFR3. Drop plug and close stage tool w/2200 PSI - plug held. Circulate 110 bbls to surface. Plug down @ 9:30 PM on 03-12-02. Rig down cementers. Set slips. Cut off casing. Release rig. Install wellhead.

Certified Return Receipt# 7001 0320 0001 0934 5179

14. Thereby certify that the foregoing is true and correct							
Name (Printed/Typed)	Title						
Trudy Grubelnik		Production Technician					
Signature De		March 19, 2002					
THIS SPACE FOR FEDERAL OR STATE USE							
Approved by /s/ Brian M. Davis		Title _ands and Mineral Resources	Date APR 1 0 2002				
Conditions of approval, if any, are attached. Approval of this notice does neertify that the applicant holds legal or equitable title to those rights in the which would entitle the applicant to conduct operations thereon.	not warrant or subject lease	Office					
Title 18 U.S.C. Section 1001 makes it a crime for any person knowingly on	ad will Giller to a	make to an illustration of the TT					

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.