Budget Bureau 42-R358.4
Approval expires 12-31-55.

Form 9-331a
(Feb. 1951)

FEB 2 1956
(SEC) P. T. McGRATH
DISTRICT ENGINEER

22

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Roswell, New Mex.
Lease No. SF-078515
Unit Torreon

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL	X		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

RECEIVED
FEB 5 1956
U. S. GEOLOGICAL SURVEY
FARMINGTON, NEW MEXICO

February 2, 1956

Well No. 1 is located 1980 ft. from {N/S} line and 660 ft. from {E/W} line of sec. 22

NW/4 SW/4 of 22 (¼ Sec. and Sec. No.) T-18-N (Twp.) R-4-W (Range) NMPM (Meridian)

Wildcat (Field) Sandoval County (County or Subdivision) New Mexico (State or Territory)

The elevation of the derrick floor above sea level is ..... ft.
Ground level 6378 feet, ungraded

RECEIVED
FEB 23 1956
OIL CON. COM.
DIST. 3

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

A total depth of 7520 feet was reached in a 9-inch hole on January 31, 1956. On February 2, 1956 verbal permission was obtained from Mr. P. T. McGrath of the U. S. Geological Survey office, Farmington, New Mexico, to plug and abandon this well in the following manner: 40 sacks neat cement at 4450 to 4550 feet or top of the Entrada formation, 40 sacks cement at 3700 to 3800 feet or the top of the Morrison sand formation, 40 sacks neat cement at 950 to 1050 feet, 20 sacks cement in the bottom of 10 3/4-inch surface casing at 422 feet, and 20 sacks cement in top of 10 3/4-inch surface casing. An appropriate sign and marker will be placed at well site. The location will be restored as nearly as possible to its original status and the U. S. Geological Survey office in Farmington, New Mexico will be notified of the completion date. No commercial shows of oil or gas were encountered during the drilling of this well.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Reynolds Mining Corporation
Oil and Gas Division
Address 152 1/2 East 9th Street
Post Office Box 1328
Durango, Colorado

By C. J. Eskridge, Jr.
Title District Petroleum Engineer