


(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYLand Office **Santa Fe, N.M.**
Lease No. **ST 07992-A**
Unit _____

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	☒	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

April 19, 1957

Well No. **1** is located **742** ft. from **SE** line and **1967** ft. from **WE** line of sec. **35**
SE SW 35 **24N** **7W** **104W**
($\frac{1}{4}$ Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Wildcat **Sandoval** **New Mexico**
(Field) (County or Subdivision) (State or Territory)

The elevation of the ~~land surface~~ is **6660** ft. (approx. ground)

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate reworking jobs, cementing points, and all other important proposed work)

1. Drill 12-1/4" hole to 200'±.
2. Run and cement 8-5/8" casing at 200'± with 150 sacks construction cement.
3. Drill 7-7/8" hole to 5650'± (Morrison)
4. If commercial production is obtained a supplementary notice will be filed, otherwise plug and abandon in accordance with U.S.G.S. regulations.

IT IS REQUESTED THAT ALL INFORMATION ON THIS WELL BE KEPT CONFIDENTIAL UNTIL WELL IS COMPLETED.

Surface formation is Upper Cretaceous

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **SHELL OIL COMPANY**
Address **108 North Railroad Avenue**
Farmington, New Mexico
By **B. W. Shepard**
Title **E. M. Shepard**
Exploitation Engineer

R.5W. N.M.P.M.

T.21N.

35

N

SEE FIELD NOTES
FOR CHECK ANGLE



ELEVATION DATA

GROUND
MATT
D.F.
K.B.
B.M. 6888.0
45.0 HIGHER THAN
GRADED GROUND AT
HANCOCK-BROWN NO.1

DESTROYED

2629.4' RECORD

742'
697'

N.89°29'W.

2629.4' RECORD

694.3' - N 1/4 COR. SEC. 2, T.20N., R.5W. N.M.P.M. (RECORD)

REFERENCE POINT DATUM-

⊙ = G.L.O. BRASS CAP FOUND

- 1"X2" STAKES SET AT 10' N., S., E., & W. OF LOC. (ORIGINAL)
- 1"X2" HUBS & 3' FLAG SET AT 100' N., & 150' S., E., & W. OF LOC. (ORIGINAL)
- 1"X2" HUB & 10' FLAG SET AT ORIGINAL LOC.
- 1"X2" HUB & 3' FLAG MARKED R.P.-100' N. = NEW LOC. BEING 1987' E. & 742' N. OF THE SW. COR. OF SEC. 35, T.21N., R.5W. N.M.P.M.
- 1"X2" HUB & 3' FLAG BEARS WEST A DISTANCE OF 150' FROM ORIGINAL LOC. FOR B.M.

This is to certify that the above plat was prepared from field notes of an actual survey made under my supervision on April 16, 1957, and that the same is true and correct to the best of my knowledge and belief.

April 19, 1957

John A. Kroeger
Reg. Land Surveyor-John A. Kroeger
B.M. Reg. No. 1941

Drawn By: A.C.T.

Checked By: *JAK*

Date: 4/19/57

SHELL OIL COMPANY

Scale 1" = 1000'

LOCATION OF SHELL HALL NO. 1

SANDOVAL COUNTY, N.M., SEC. 35, T.21N., R.5W., N.M.P.M.