Form 9-331 a (Feb. 1951)

2	3	
 		×

(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR **GEOLOGICAL SURVEY**

Land Office	Santa Pe
Lease No	SF-080097
Unit	

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	hM
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	-
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	-
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL		.
(INDICATE ABOVE BY CHECK N	MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)	-!
	August 7	9.57
Sendovel 22-7		~ ~
'ell No. 1-23 is located 1980 ft. fr	rom. $\left\{S\right\}$ line and $\left\{S\right\}$ line of sec	23
(½ Sec. and Sec. No.) (Twp.)	(Range) (Meridian)	
warman and a series	unty or Subdivision) (State or Territory)	-
he elevation of the	a level is 6401 ft.	
DE.	TAILS OF WORK	
- -		
tate names of and expected depths to objective sands; sho	w sizes, weights, and lengths of proposed easings; indicate mudding jobs.	cement
ing points, and	d all other important proposed work)	
ing points, and	i all other important proposed work)	4
ing points, and D 5975'. Pulled the	and set Baker CI retainer at 5795'. Squ	d 0.5_
ing points, and ID 5975'. 193 5795'. Pulled the weeks 5014-20 w/45 sx reg. 3D 30	and set Baker CI retainer at 5795'. Sept 1004. Min 25004. Max, Final and Stdg 400	4 04. 52*
ing points, and the parts 501/6-20 w/45 ex reg. 3D 30 to comp 6:30 ms 7-31-57. Forf 2	s and set Baker CI retainer at 5795'. Squ 100f. Him 2500f. Ham, Final and Stdg 400 I holes at 4758', set Baker retainer at 47	d 04. 52°
ing points, and TD 5995'. Pulled the serie 5014-20 w/45 ex reg. RD 30 to comp 6:30 mm 7-31-57. Forf 2 and equal w/150 em reg. RD 26006.	and set Baker CI retainer at 5795'. Sept 1004. Min 25004. Max. Final and Stdg 400 holds at 4756', set Baker retainer at 47 IF 15004. Final and Stdg 20084. Cat c	d 04. 52' ire
ing points, and D 5975'. Pulled the serie 5014-20 u/45 ex reg. RD 30 lub comp 6:30 ms 7-31-57. Perf 2 and equal u/150 ms reg. RD 26006. To surface. Job complete 5 PM 8-	and set Baker CI retainer at 5795'. Squ 1004. Min 25004. Max, Final and Stdg 400 I holes at 4756', set Baker retainer at 47 IP 15000. Final and Stdg 20000. Cut c 1-57. Brid retainer at 4752' and cleaned	d 04. 52' ire
ing points, and D 5975'. Pulled the serie 5014-20 w/45 ex reg. RD 30 to comp 6:30 ms 7-31-57. Forf 2 and equal w/150 ms req. RD 26006.	and set Baker CI retainer at 5795'. Squ 1004. Min 25004. Max, Final and Stdg 400 I holes at 4756', set Baker retainer at 47 IP 15000. Final and Stdg 20000. Cut c 1-57. Brid retainer at 4752' and cleaned	d 04. 52' ire
ing points, and D 5975'. Pulled the serie 5014-20 u/45 ex reg. RD 30 lub comp 6:30 ms 7-31-57. Perf 2 and equal u/150 ms reg. RD 26006. To surface. Job complete 5 PM 8-	and set Baker CI retainer at 5795'. Squ 1004. Min 25004. Max, Final and Stdg 400 I holes at 4756', set Baker retainer at 47 IP 15000. Final and Stdg 20000. Cut c 1-57. Brid retainer at 4752' and cleaned	d 04. 52' ire
ing points, and D 5975'. Pulled the serie 5014-20 u/45 ex reg. RD 30 lub comp 6:30 ms 7-31-57. Perf 2 and equal u/150 ms reg. RD 26006. To surface. Job complete 5 PM 8-	and set Baker CI retainer at 5795'. Squ 1004. Min 25004. Max, Final and Stdg 400 I holes at 4756', set Baker retainer at 47 IP 15000. Final and Stdg 20000. Cut c 1-57. Brid retainer at 4752' and cleaned	d 04. 52' ire
ing points, and D 5975'. Pulled the serie 5014-20 u/45 ex reg. RD 30 lub comp 6:30 ms 7-31-57. Perf 2 and equal u/150 ms reg. RD 26006. To surface. Job complete 5 PM 8-	and set Baker CI retainer at 5795'. Squ 1004. Min 25004. Max, Final and Stdg 400 I holes at 4756', set Baker retainer at 47 IP 15000. Final and Stdg 20000. Cut c 1-57. Brid retainer at 4752' and cleaned	d 04. 52' ire
ing points, and D 5975'. Pulled the serie 5014-20 u/45 ex reg. RD 30 lub comp 6:30 ms 7-31-57. Perf 2 and equal u/150 ms reg. RD 26006. To surface. Job complete 5 PM 8-	and set Baker CI retainer at 5795'. Squ 1004. Min 25004. Max, Final and Stdg 400 I holes at 4756', set Baker retainer at 47 IP 15000. Final and Stdg 20000. Cut c 1-57. Brid retainer at 4752' and cleaned	d 04. 52' ire
ing points, and D 5975'. Pulled the serie 5014-20 w/45 ex reg. RD 30 lub comp 6:30 mm 7-31-57. Perf 2 and equal w/150 mm reg. RD 26006. To surface. Job complete 5 PM 8-	and set Baker CI retainer at 5795'. Squ 1004. Min 25004. Max, Final and Stdg 400 I holes at 4756', set Baker retainer at 47 IP 15000. Final and Stdg 20000. Cut c 1-57. Brid retainer at 4752' and cleaned	d 04. 52' ire
ing points, and ID 5975'. Pulled the serie 5014-20 w/45 ex reg. RD 30 lub comp 6:30 ms 7-31-57. Perf 2 and equal w/150 ms reg. RD 26006. To surface. Jub complete 5 PM 8-	and set Baker CI retainer at 5795'. Squ 1004. Min 25004. Max, Final and Stdg 400 I holes at 4756', set Baker retainer at 47 IP 15000. Final and Stdg 20000. Cut c 1-57. Brid retainer at 4752' and cleaned	d 04. 52' ire
ing points, and the System of Superior Sulfi-20 w/45 ex reg. RD 30 hub comp 6:30 ms 7-31-57. Perf 2 and equal w/150 em reg. RD 26006. To surface. Jub complete 5 PM 8-to 5795°. Prep to parf and fram	i and set Baker CI retainer at 5795'. Squ 100f. Min 2500f. Max, Final and Stdg 400 i holes at 4758', set Baker retainer at 47 IF 1500f. Final and Stdg 2000f. Cat c 1-57. Brid retainer at 4752' and cleaned Gallup formation.	d 04. 52' ire
ing points, and the System of Superior Sulfi-20 w/45 ex reg. RD 30 hub comp 6:30 ms 7-31-57. Perf 2 and equal w/150 em reg. RD 26006. To surface. Jub complete 5 PM 8-to 5795°. Prep to parf and fram	and set Baker CI retainer at 5795'. Squ 1004. Min 25004. Max, Final and Stdg 400 I holes at 4756', set Baker retainer at 47 IP 15000. Final and Stdg 20000. Cut c 1-57. Brid retainer at 4752' and cleaned	d 04. 52' ire
ing points, and ID 5975°. Pulled the perfe 5016-20 w/45 ex reg. RD 30 feb comp 6:30 as 7-31-57. Ferf 2 and equel w/150 as reg. RD 26006. to surface. Jub complete 5 PM 8-to 5795°. Prep to parf and fract	and set Baker CI retainer at 5795'. See 1004. Min 25004. Max. Final and Stdg 400 holes at 4758', set Baker retainer at 47 IP 15004. Final and Stdg 20004. Cat a 1-57. Brid retainer at 4752' and cleaned Gallup formation.	d 04. 52' ire
In 5975'. Pan 5795'. Pulled the parfe 5016-20 w/45 ex reg. 3D 30 leb comp 6:30 ms 7-31-57. Parf 2 ms equal w/150 ms reg. 3D 26006. To surface. Jub complete 5 PM 5-to 5795'. Prop to parf and fram a function of the surface of the sur	and set Baker CI retainer at 5795'. See 1006. Min 25006. Max, Final and Stdg 400 holes at 4758', set Baker retainer at 47 IF 15006. Final and Stdg 20006. Cat a 1-57. Brid retainer at 4732' and cleaned Gallup formation.	d 04. 52' ire
In 5975°. PDD 5795°. Pulled the perfe 5016-20 w/45 ex reg. RD 30 hab comp 6:30 ms 7-31-57. Perf 2 and equal w/150 ms reg. RD 24006. To surface. Ash complete 5 PM 5-to 5795°. Prep to parf and fraction of the first	and set Baker CI retainer at 5795'. See 1006. Min 25006. Max, Final and Stdg 400 holes at 4758', set Baker retainer at 47 IF 15006. Final and Stdg 20006. Cat a 1-57. Brid retainer at 4732' and cleaned Gallup formation.	d 04. 52' ire
I understand that this plan of work must receive approximately and fraction of the following states of	and set Baker CI retainer at 5795'. See 1006. Min 25006. Max, Final and Stdg 400 holes at 4758', set Baker retainer at 47 IP 13006. Final and Stdg 20006. Cat a 1-57. Brid retainer at 4752' and cleaned Gallup formation. valin writing by the Geological Survey before operations have be tempted to the company of the compan	d 04. 52' ire
ing points, and ID 5975'. Pulled the perfe 5016-20 w/45 ex reg. RD 30 feb comp 6:30 as 7-31-57. Ferf 2 and equal w/150 am reg. RD 26006. to surface. Jub complete 5 PM 8-to 5795'. Prop to parf and fract	and set Baker CI retainer at 5795'. See 1006. Min 25006. Max, Final and Stdg 400 holes at 4758', set Baker retainer at 47 IP 13006. Final and Stdg 20006. Cat a 1-57. Brid retainer at 4752' and cleaned Gallup formation. valin writing by the Geological Survey before operations have be tempted to the company of the compan	d 04. 52' ire
I understand that this plan of work must receive approximately and fraction of the company and company are also as a company and company are a company are a company and company are a company and company are a company are a company and company are a company are a company and company are a company are a company and company are a company	and set Baker CI retainer at 5795'. See 1006. Min 25006. Max, Final and Stdg 400 holes at 4758', set Baker retainer at 47 IP 13006. Final and Stdg 20006. Cat a 1-57. Brid retainer at 4752' and cleaned Gallup formation. valin writing by the Geological Survey before operations have be tempted to the company of the compan	d 04. 52' ire