

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

370

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Jicarilla

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Humble Dakota

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Wildcat

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

21-T22N-R2W

12. COUNTY OR PARISH

Sandoval

13. STATE

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT..." for such proposals.)

1. OIL ☒ WELL GAS ☐ WELL ☐ OTHER

2. NAME OF OPERATOR
Lynco Oil Corporation

3. ADDRESS OF OPERATOR
5290 DTC Parkway Bldg. #2 Englewood, Colorado 80111

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

875 FNL and 910 FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

7328 GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETION ☐

ABANDON* ☒

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) ☐

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT* ☒


(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

We propose to plug and abandon as follows:

Set plug #1 at 4450-4600 covering existing perforations. Perforate @ 4325 and set cement retainers at 4225. Squeeze top of Cliff House with sufficient volume to cover 100' behind casing. Perforate at 2750 and set cement retainer at 2650. Squeeze with sufficient volume to cover 100' behind csg. Perforate 2250 and set cement retainer at 2250. Squeeze with sufficient volume of cement to cover 300' inside and outside of casing. Set plug #5 from surface to 130' in surface casing with well marker.

Operations to commence in approximately 30 days depending on rig availability.



18. I hereby certify that the foregoing is true and correct

SIGNED

James M. Ray

TITLE Field Superintendent

DATE 7-18-78

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED
DATE

JUL 19 1978

U. S. GEOLOGICAL SURVEY
DURANGO, COLO.

*See Instructions on Reverse Side