

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

14 20 0603 9884

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Navajo Allotted

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Cabezon

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Wildcat

11. SEC., T., E., M., OR BLK. AND SURVEY OR AREA

Sec 29, T17N, R4W, N4PY

12. COUNTY OR PARISH

Sandoval

13. STATE

New Mexico

1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ DRY

2. NAME OF OPERATOR

REFINERS PETROLEUM CORP.

3. ADDRESS OF OPERATOR

900 Bank of New Mexico Building, Albuquerque, New Mexico

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*

See also space 17 below.)
At surface

1980' FWL, 1980' FEL

14. PERMIT NO.

USGS 6-27-71

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6423' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON* ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) ☐

REPAIRING WELL ☐

ALTERING CASING ☐


ABANDONMENT* ☒

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Moved in completion rig. Tested casing with 1700# psi for 30 minutes. Held okay. Perforated with two shots per foot from 3870' to 3878'. Swabbed well and recovered water with trace of oil. Re-perforated from 3890' to 3900'. Swabbed well and recovered water with trace of oil.

Obtained verbal approval to plug and abandon well from Mr. Jerry Long with U.S.G.S. Spotted 15 sack plug in 5 1/2" casing from 3932' to 3823'. Shot off casing at 2994'. Spotted the second plug from cut-off at 2994' to 2675', third plug at 1325' to 1425', fourth plug at 650' to 750', fifth plug at 100' to 150'. Plugging completed 7-20-71. Installed dry hole marker and 20 sack cement plug in surface 7-22-71.



RECEIVED

JUL 30 1971

U. S. GEOLOGICAL SURVEY
DENVER, COLO.

18. I hereby certify that the foregoing is true and correct

Original signed by

SIGNED Morris B. Jones

TITLE

Petroleum Engineer

DATE

7-22-71

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

St. George

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.


Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE: 1963-O-685229

847 - 485

RECEIVED



U.S. DEPT. OF THE INTERIOR
BUREAU OF LAND MANAGEMENT