

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Form Approved.  
Budget Bureau No. 42-R1424

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐

2. NAME OF OPERATOR

El Paso Exploration Company

3. ADDRESS OF OPERATOR

Box 289 Farmington, New Mexico 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1800'S, 1650'E

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☒  
(other) ☐

SUBSEQUENT REPORT OF:

☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☒  
☐

RECEIVED

JUN 03 1982

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

May 19-21

MOL & RU. Picked up 1 1/4" IJ tubing work string and circulated well. Spotted a 15 sx (17 ft<sup>3</sup>) cement plug across perforations. Displaced 5 sx into perforations leaving plug in casing from 3199' to 3027'. Spotted 5 sx cement plug across Fruitland top (2962') from 3012' to 2840'. Perforated w/ 2 shots at 2782' 50' below top of Ojo Alamo (2732'). Spotted a 35 sx (40 ft<sup>3</sup>) cement plug to cover Ojo and squeeze 30 sx through perforations leaving a cement plug from 2782' to 2610'. Perforated w/ 2 shots at 190' and spot 74 sx (85 ft<sup>3</sup>) of cement and squeezed leaving a plug from 190' to 40'. Spotted a 10 sx (12 ft<sup>3</sup>) plug in surface tubing and installed a plug and abandon marker. Spotted 9.2 lb/gal mud between cement plugs.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

*CRB*

TITLE

Production Engineer

DATE

June 3, 1982

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

OPERATOR

APR 24 1987

APPROVED  
AS AMENDED

NOV 1 1981

M. MILLENBACH  
AREA MANAGER