Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR

FORM APPROVED Budget Bureau No. 1004-0135

BUREAU OF LAND MANAGEMENT	Expires: March 31, 1993
	5. Lease Designation and Serial No.
SUNDRY NOTICES AND REPORTS ON WELLS	NM14240
Do not use this form for proposals to drill or to deepen or reentry to a different recommend	6. If Indian, Allottee or Tribe Name
Use "APPLICATION FOR PERMIT—" for such proposals	
	-
SUBMIT IN TRIPLICATE	7. If Unit or CA, Agreement Designation
I. Type of Well	-
☐ Well ☐ Well X Other Gas Storage Observation Well	8. Well Name and No.
2 Name of Operator	San Ysidro
PNM Gas Services 3 Address and Telephone No.	9. API Well No
	#4
603 W. Elm, P. O. Box 4750, Farmington, NM 87499 4 Location of Well (Footage, Sec., T., R., M., or Survey Description)	10. Field and Pool, or Exploratory Area
	Azua Zarca
2015' FSL & 1785' FWL	11. County or Parish, State
Sec. 20, T-15, R-1E	Sandoval Co., NM
	!
CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPOR	RT OP OTHER DATA
TYPE OF SUBMISSION	I, OR OTHER DATA
THE OF ACTION	
X Notice of Intent	Change of Plans
Recompletion	New Construction
Subsequent Report Plugging Back	Non-Routine Fracturing
Casing Repair	Water Shut-Off
Final Abandonment Notice Altering Casing	Conversion to Injection
<u>X</u> Other	Dispose Water
	(Note: Report results of multiple completion on W.
13 Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting a give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work are	Completion or Recompletion Report and Log form
give subsurface locations and measured and true vertical depths for all markers and give pertinent dates, including estimated date of starting a	my proposed work. It went is directionally drille
12/3/95 - Pull out of hole with 2 3/8" tubing and packer. Run in h	ole with bit and casing
Scraper () 1/2, 10.0# CSg.) to PBID of /435'. Trip out of holo wi	l+h h-1+ 1
run in hole with redressed Model "G" production packer. Set packer	tension at ᆂ 2200'.
Test annulas to 300 psi for 30 minutes. Load annulus with packer f location.	luid and move off
TOCACIOII.	
DE OF	
DECEINED	0 9
	70 × 81
DEC - 1 1295	81 M I 95 NOV
· read 177	ECE MA
	9 AE
	G P L<
	70 M RED
•	L ROOM PH 2: 51
	BI M MAIL ROOM 95 NOV -9 PM 2:51
4 I hereby/certily that the foregoing is true and correct	
Signed fisse wars Title Se Engineer	_ Date _1/9/95
(This space for Federal or State office use)	
Approved by Approved by Title Thou, Earlies and Willieta, Hesoulties	\$1017 2 A 100B
Conditions of approval, if any:	Date <u>NOV 3 0 1995</u>