63 63

Form 9-331 (May 1963)							Budget Bureau No. 42-R1424. 5. LEASE DESIGNATION AND SHRIAL NO. NH 05564.74		
SUNDRY NOTICES AND REPORTS ON THIS (Do not use this form for proposals to drill or to deepen or plug of the different behavior. Use "APPLICATION FOR PERMIT—" for such proposals.						6. IF INDIAN, ALLOTTER OR TRIBE NAME Pederal			
OIL GAS		Dage	MAY	13 1975		7. UNIT AGREEMENT NAM	i n		
2. NAME OF OPERAT	OR	- 1/34P-i-	T MMI	T 0 101 4	1	8. FARM OR LEASE NAME	j		
RESESE & JONES OIL CON. COM.						HACK Federal			
3. Address of open		Building, Albuq	7	SI Page	871 02	9. WELL NO.			
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface					10. FIELD AND POOL, OR WILDCAT				
1980* fal, 1980* fwl						11. SEC., T., E., M., OR BLK. AND SURVEY OR AREA			
						Sec 36, 1201,	rak, mer		
14. PERMIT NO.		15. ELEVATIONS (Show whe	ether DF, RT, GR	, etc.)		12. COUNTY OR PARISH	13. STATE		
U.S.G.S. 3-31-75 6961 GR, 6973 K			3 B			Sandoval	New Mexic		
16.	Check A	opropriate Box To India	ate Nature	of Notice, Rep	ort, or C	ther Data			
	NOTICE OF INTER	NTION TO:			SUBSEQU	ENT REPORT OF:			
TEST WATER SE	IUT-OFF	PULL OR ALTER CASING]	WATER SHUT-OFF		REPAIRING W	BLL		
				FRACTURE TREATM	ENT	ALTERING CA	SING		
SHOOT OR ACIDIZE ABANDON* SHOOTING OR ACIDIZING						ABANDONMEN	T		
REPAIR WELL CHANGE PLANS (Other)									
(Other) (Note: Report results of multiple completion Completion or Recompletion Report and Log						of multiple completion of etion Report and Log for	n Well m.)		
proposed wor nent to this w	k. If well is directi ork.) *	ERATIONS (Clearly state all ponally drilled, give subsurfa	ce locations a	na measurea ana	true vertica	i depths for an markers	of starting any and zones perti-		
1. 53	sacks from	3100 Sin 1:0	(Censent (O') Exeti (O') Dake	reda	ollows				
2. 31	# Secre Tlam	4500 - 4600' (10	and make	/					

3. 34 sacks from 2550 - 2650* (100*) Hancos
4. 34 sacks from 860 - 960* (100*) La Ventana
5. 17 sacks from 175 - 225* (50*) Bottom of surface casing
6. 14 sacks from 0 - 30* (30*) Top of surface casing

Installed dry hole marker and cleaned location on May 2, 1975.

8. I hereby certif Obat the foregoing is true and correct SIGNED MORRIS B. JONES	TITLE _	Petroleus Engineer	DATE _	May 2, 1975
(This space for Federal or State office use)				
APPROVED BYCONDITIONS OF APPROVAL, IF ANY:	TITLE _		DATE	

*See Instructions on Reverse Side

St Clerky