

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL ☐ GAS WELL ☐ OTHER Water Disposal

2. NAME OF OPERATOR

FILON EXPLORATION CORPORATION c/o Minerals Management Inc.

3. ADDRESS OF OPERATOR

501 Airport Dr., Suite 210, Farmington, New Mexico 87401

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

460' FSL, 800' FEL, SEC. 11, T19N, R4W

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6656 RT

5. LEASE DESIGNATION AND SERIAL NO.

NM24961

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Federal 11C

9. WELL NO.

#2

10. FIELD AND POOL, OR WILDCAT

Gallup

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

SEC. 11, T19N, R4W

12. COUNTY OR PARISH 13. STATE

Sandoval

N.M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

☐
☐
☐
☐

PULL OR ALTER CASING

☐
☐
☐
☐

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

☐
☐
☒
☐

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

☐
☐
☐
☐

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

9-28-75

Perforate 5 1/2" casing 3177-3048, 3206-3270, 3350-3428, 3470-3596 With ISPF.

9-29-75

Selectively acidize perforations w/packer & bridge plug.

Acidize 3470-3596 with 2500 gals. HF acid

Acidize 3350-3428 with 1500 gals. HF acid

Acidize 3206-3270 with 1500 gals. HF acid

Acidize 3048-3177 with 2500 gals. HF acid

9-30-75

Ran 2 7/8" internally coated plastic coated tubing & packer. Set packer at 3003'. Fluid on 2 7/8"-5 1/2" annulus treated w/corrosion inhibitor. Well shut in.

18. I hereby certify that the foregoing is true and correct

SIGNED

J. Arnold Shell

Area Manager

TITLE Minerals Management Inc DATE 10-6-75

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: