

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE\*  
(Other instructions on reverse side)

Form approved.  
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		5. LEASE DESIGNATION AND SERIAL NO. NOO-C-1420-2717	
2. NAME OF OPERATOR FILON EXPLORATION CORPORATION		6. IF INDIAN, ALLOTTEE OR TRIBE NAME Navajo Allotted	
3. ADDRESS OF OPERATOR c/o Minerals Management Inc. 501 Airport Dr., Suite 210, Farmington, New Mexico 87401		7. UNIT AGREEMENT NAME	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface  330' FNL, 330' FEL, SEC. 14, T19N, R4W		8. FARM OR LEASE NAME Navajo 14C	
14. PERMIT NO.		9. WELL NO. 01 #1	
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 6662 RT		10. FIELD AND POOL, OR WILDCAT Undesignated Entrada	
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA SEC. 14, T19N, R4W	
		12. COUNTY OR PARISH Sandoval	
		13. STATE N.M.	

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

Spud & surface casing

REPAIRING WELL

ALTERING CASING


ABANDONMENT\*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

10-20-75 Spud 15" hole at 10PM. Drill to 204'.

10-21-75 Ran 182' 10 3/4" 40.5# K-55 ST&C casing. Set at 197'.  
Cement with 200 sacks Class "B" w/2% CaCl. Circulate cement.  
WOC 12 hours. Test to 500 psi-OK



NOTE: THIS IS A TIGHT HOLE.

18. I hereby certify that the foregoing is true and correct.

SIGNED

*J. Arnold Shell*

Area Manager

TITLE Minerals Management Inc DATE 10-22-75

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: