

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well  gas well  other \_\_\_\_\_

2. NAME OF OPERATOR  
Kirby Exploration Company

3. ADDRESS OF OPERATOR  
Box 1745 Houston, Texas 77001

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1190' FNL and 1450' FEL  
AT TOP PROD. INTERVAL: same  
AT TOTAL DEPTH: same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF	<input type="checkbox"/>		<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>		<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>		<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>		<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>		<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>		<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>		<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>		<input checked="" type="checkbox"/>
(other)	<input type="checkbox"/>		<input type="checkbox"/>

5. LEASE  
NM 303

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME  
Bradshaw Federal

9. WELL NO.  
1

10. FIELD OR WILDCAT NAME  
Wildcat *Chaco*

11. SEC., T., R., M. OR BLK. AND SURVEY OR AREA  
Sec 27, T22N, R6W

12. COUNTY OR PARISH  
Sandoval

13. STATE  
New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
7083 GL and 7095 KB

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

The subject well was thoroughly tested and proved to be non-commercial. It was plugged as follows: plug from 2100' to 1900' with 25 sk class "B" cement; plug from 1650' to 1450' with 25 sack class "B" cement; perforate 4 squeeze holes at 1300' and squeeze with 60 sacks class "B" cement, leaving cement top at 1100. Allow to set 2 hours. Perforate 4 squeeze holes at 150' and squeeze with 25 sk class "B" cement. Plug from 60' to top of surface pipe with 10 sack class "B" cement. Squeeze 5 sack class "B" cement between 8 5/8" surface and 4 1/2" production casing.

Installed dry hole marker. Levelled location, now ready to seed.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED William T. Jones TITLE Agent DATE 7-78

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side

MAY 15 1978

U. S. GEOLOGICAL SURVEY  
DURANGO, COLO.

*State*