

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		5. LEASE DESIGNATION AND SERIAL NO. NOO-C-14-20-5796
2. NAME OF OPERATOR Dome Petroleum Corporation		6. IF INDIAN, ALLOTTEE OR TRIBE NAME Navajo
3. ADDRESS OF OPERATOR Minerals Management Inc., Suite 105, 501 Airport Drive, Farmington, New Mexico 87401		7. UNIT AGREEMENT NAME
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 990' FSL, 2100' FEL, SEC. 19, T21 N, R5W		8. FARM OR LEASE NAME Navajo Allotted 19-21-5
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.) 7007' GR, 7019' KB	9. WELL NO. 1
		10. FIELD AND POOL, OR WILDCAT Wildcat
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA SEC. 19, T21N, R5W NMPM
		12. COUNTY OR PARISH Sandoval
		13. STATE N.M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐PULL OR ALTER CASING ☐FRACTURE TREAT ☐MULTIPLE COMPLETE ☐SHOOT OR ACIDIZE ☐ABANDON* ☐REPAIR WELL ☐CHANGE PLANS ☐(Other) ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐REPAIRING WELL ☐FRACTURE TREATMENT ☐ALTERING CASING ☐SHOOTING OR ACIDIZING ☐ABANDONMENT* ☐(Other) Spud & Set Surface Casing ☒

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1-4-78 Spudded 13 1/4" hole at 3:30 p.m. Ran 5 jts (183') 9 5/8", 36#, K-55, ST&C and LT&C casing set at 195' KB. Cemented with 200 sx Class "B", 2% CaCl. Plug down at 12:00 midnight. Circulated cement.

1-5-78 Pressure tested casing to 500 psi, 30 minutes--OK.

CONFIDENTIAL

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Area Manager

Minerals Management Inc.

DATE

1-5-78

(This space for Federal or State office use)


APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side



JAN 9 1978

U.S. GEOLOGICAL SURVEY