UNITED STATES DEPARTMENT OF THE INTERIOR

DEPAR	TMENT OF THE	INTERIOR	CASW 668
G	EOLOGICAL SUR	VEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
			- Federal - In the Fede
SUNDRY NOTIC	CES AND REP	ORTS ON WELLS	7. UNIT AGREEMENT NAME
Do not use this form for pro	onosals to drill or to de	epen or plug back to a different	
eservoir. Use Form 9-331-C	for such proposals.)		8. FARM OR LEASE NAME
1. oil gas	X other		Boling Federal 5 253
well well			9. WELL NO. 19 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5
2. NAME OF OPERATO Petro-Lewis C			10. FIELD OR WILDCAT NAME
			Southwest Media Entrada
3. ADDRESS OF OPER P.O. Box 509.	Levelland, T	exas 79336	11. SEC., T., R., M., OR BLK, AND SURVEY
		N CLEARLY. See space 17	AREA (1) A CARACTER AND A CARACTER A
below.)			Sec. 22, T19N, R3W
	0' FNL & 2160)' FWL	12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INT	TERVAL: 5425 *		Sandoval N.M.
AT TOTAL DEPTH:			14. API NO. ខ្លុំខ្លុំ ត ខ្ញុំខ្លែក
		ATE NATURE OF NOTICE,	
REPORT, OR OTHE	K DATA		15. ELEVATIONS (SHOW DF, KDB, AND V
REQUEST FOR APPROV	AL TO: SUB	SEQUENT REPORT OF:	6869' GR
TEST WATER SHUT-OFF			
FRACTURE TREAT	Ō		
SHOOT OR ACIDIZE			
REPAIR WELL PULL OR ALTER CASIN	ue 📙		(NOTE: Report results of multiple completion or a change on Form 9~330.)
MULTIPLE COMPLETE		H	
CHANGE ZONES			
ABANDON*		X	
(other) Spud & (Sement Surface	2	A STORES
17. DESCRIBE PROPOS	SED OR COMPLETE	OPERATIONS (Clearly sta	ate all pertinent details and give pertinent da
including actimated	l date of starting an	y proposed work. If well is Il markers and zones pertine	directionally diffled, give subsurface locations
measured and true	vertical deptils for a	ii markers and zones pertin	ent to this work.)
1-27-78 -	Soud in hole	with 15" bit.	COM.
			1 48 A 3
1-28-78 -	Drilled 15"	hole to 508'. Rig	ged up and ran Texas Partern Gu
1 20 70	Shoe 11 ioi	nts 10-3/4" OD	32.75#, H-40, Long Star AP, EW
	ST&C, R-3 ca	sing, to 491' KB.	Ran 5 centralizers, one every
	collar.	_	그 그 그 그 그 일부터 한번 그 한 회사소. 그
1-29-78 -	Rigged up Ha	lliburton and ceme	ented surface with 400 sx. Class
	"B" 4% gel,	2% CACL ₂ , at 200 P	SI. Circulated 47 bbls. cement
	out. WOC-4	hrs.	701 201 201 30 3/4" COW type "S
	Installed sl	ip-on Bradenhead W	WKM 10"-3MX 10-3/4" SOW, type "S
	W/2-2" LPO.	WOC - 18 hrs.	
Subsurface Safety Valve	e: Manu. and Type $_$		Set @
18. I hereby certify that	the foregoing is true	and correct	
4/20/			Foreman January 30, 1978
SIGNED TOTAL	suply	TITLE Sr. Drlg. F	DATE
		This space for Federal or State o	office use)
_		T1T1 F	DATE IN PORT OF THE
APPROVED BY TITLE CONDITIONS OF APPROVAL, IF ANY:		THE WEINER	
			ECD 1 1076
			% 13750 T. 121.0 €