

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☐ other ☐
well well

2. NAME OF OPERATOR
DOME PETROLEUM CORPORATION

3. ADDRESS OF OPERATOR 501 Airport Drive,
Suite 107, FARMINGTON, NEW MEXICO 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 660' FNL, 500' FWL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF	<input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>	<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>	<input type="checkbox"/>

(other) RUN PRODUCTION CASING

5. LEASE
NOO-C-14-20-3668

6. IF INDIAN, ALLOTTEE OR TRIBE NAME
NAVAJO, ALLOTTED

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
DOME NAVAJO 29-21-7

9. WELL NO.
1

10. FIELD OR WILDCAT NAME
WILDCAT

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
SEC. 29, T21N, R7W

12. COUNTY OR PARISH 13. STATE
SANDOVAL NEW MEXICO

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
6802 GR.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Ran 149 joints (6180') 7", 26#, 23# & 20#, K55 ST&C Casing. Cemented with 370 sacks 65/35 Pozmix, 6% Gel and 10# Gilsonite/sack. Followed with 300 sacks Class "B" Cement with 10% salt. Plug down at 5:00 P.M. 3/13/80. Released rig at 10:00 P.M. 3/13/80.

ACCEPTED

BY CRB

Subsurface Safety Valve: Manu. and Type _____ Ft.


18. I hereby certify that the foregoing is true and correct

SIGNED H. D. Hollingsworth TITLE DRLG. & PROD. FOREMAN DATE 3/14/80

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side



MAR 17 1980

U. S. GEOLOGICAL SURVEY
DURANGO, COLO.