BW 184 NO

5. LEASE

ED STATES

DEPARTS INTO SETHE LITERIOR	NOO-C-14-20-5385
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME Navajo
SUNDRY NOTICES AND REPORTS ON WELLS Or not use this form for proposals to and general or plus page to a different	7. UNIT AGREEMENT NAME
Do not use this form for proposals to public to descen or plug back to a different eservoir. Use Form 9-331-0 for such proposals .	8. FARM OR LEASE NAME
I. C. — Res —	Dome Navajo 28-22-7
The Late of the Control	9. WELL NO.
2 MAME OF CREEKTOR	2
DOME PETROLEUM COPP.	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR Ell Alimpurt Drive,	Rusty Chacra Extension
White 114, Farmington, New Newton 87401 4. LOCATION OF WELL (REPORT LOCATION CLEARLY, See space 17	11. SEC., T., R., M., OR BLK, AND SURVEY OR AREA
pelaw)	Sec. 28, T22N, R7W
AT SÚRFACE: 1560° DSI, CICT PEL	12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL.	Sandoval New Mexico
AT TOTAL DEPTH:	14. API NO.
6. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
EQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	6704' GR
FOT WATER SHITTINES	
RACTURE TREAT	
HOOT OR ACIDIZE	a France
EPAIR WELL	(NOTE: Report results of multiple completing or zone
ULL OR ALTER CASING	change on Form Coop.
TSETTLE COMPLETE	
EANE CHY	
Spud and Set Surface Casing	1812
TO THE REPORTED OF COMPLETED OPERATIONS (C)	SED 2 9 1564
including estimated date of starting any proposed work. If well is d	irectionally drilled, give, substitute Colors and
7 DISCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly stat including estimated date of starting any proposed work. If well is d measured and true vertical depths for all markers and zones pertiner	nt to this work.)* OIL DIST. 3
Spudded 12%" hole at 9:15 p.m., 9/23/80. Drille	ed to 135'. Ran 2 jts. (129')
عَدَّر ST&C كَمَا Casing Landed at 131' G	L. Cemented with 100 sacks
Class 3" Cement with 2% CaCl. Plug down at 2:	15 a.m., 9/24/80. Circulated ceme
Spudded 12%" hole at 9:15 p.m., 9/23/80. Drille 24=. ST&C, K55 Casing. Casing landed at 131' Glasses ST&C Ement with 2% CaCl. Plug down at 2:2	
Elvi	
e at the same	
2 % C	
TOLOGICAL SCALL	
Aktor	
Subsurface Safety Valve: Manu. and Type	Set @ Ft.
18. I hereby certify that the foregoing is true and correct	
SIGNED AND STREET STREET, THE PIG. SProd. For	eman date September 24, 1980
(This space for Federal or State off	
PPROVED ES	DATE
CONDITIONS OF APPROVAL, IF ANY:	

*See Instructions on Reverse Side