

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐  
well well

2. NAME OF OPERATOR

Dome Petroleum Corp.

3. ADDRESS OF OPERATOR 501 Airport Drive,  
Suite 114, Farmington, NM 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1850' FNL, 790' FWL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON\* ☐

(other) Spud & Set Surface Casing

SUBSEQUENT REPORT OF:

☐

☐

☐

☐

☐

☐

☐

☐

☐

RECEIVED

OCT 16 1980

U. S. GEOLOGICAL SURVEY  
FARMINGTON, N. M.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Spudded 12 1/4" hole at 8:40 a.m., 10/5/80. Drilled to 140'. Ran 3 jts. (137') 8 5/8", 24#, K55, ST&C Casing. Casing landed at 138' G.L. Cemented with 90 sx. Class "B" Cement with 2% CaCl. Plug down at 3:15 p.m., 10/5/80. Circulated cement.

Subsurface Safety Valve: Manu. and Type

18. I hereby certify that the foregoing is true and correct

SIGNED H. D. HOLDINGSWORTH TITLE Drlg. & Prod. Foreman DATE Oct. 6, 1980

(This space for Federal or State office use)

APPROVED BY ACCEPTE FOR FEDERAL IF ANY:

TITLE

DATE

OCT 15 1980

\*See Instructions on Reverse Side

BY BW FARMINGTON DISTRICT

