| | UNITED STATES | 5. LEASE |
|--|--|--|
| DEPART | MENT OF THE INTERIOR | N00-C-14-20-3669 |
| GE | OLOGICAL SHEVEY | 6. IF INDIAN, ALLOTTEE OR TRIBE NAME |
| | W 5 6 5 1 00 - | Navajo Allotted - |
| SUNDRY NOTICE | es and bei ports on weiges | 7. UNIT AGREEMENT NAME |
| (Do not use this form for proporeservoir Use Form 9-331-C for | osals to drill or to deepen or plug back to a difference or such proposals.) | #/- |
| | | |
| 1. oil 🔯 gas 🗆 | other O/L COA | Dome Navajo 30-21-7 |
| 2. NAME OF OPERATOR | - O/// A | 9. WELL NO. |
| | | 10. FIELD OR WILDCAT NAME |
| Dome Petroleum 3. ADDRESS OF OPERA | COLD | Undesignated Entrada |
| | mington, New Mexico 87401 | 11. SEC., T., R., M., OR BLK. AND SURVEY OR |
| 4. LOCATION OF WELL (| REPORT LOCATION CLEARLY. See space | |
| below.) | | Sec. 30, T21N, R7W |
| . AT SURFACE: 810' | | 12. COUNTY OR PARISH 13. STATE |
| AT TOP PROD. INTER AT TOTAL DEPTH: | RVAL: | Sandoval New Mexico |
| | | 14. API NO. |
| 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA | | |
| | | 15. ELEVATIONS (SHOW DF, KDB, AND WD) |
| REQUEST FOR APPROVAL | . TO: SUBSEQUENT REPORT OF: | 67521 GR |
| TEST WATER SHUT-OFF | | |
| FRACTURE TREAT | | The state of the s |
| SHOOT OR ACIDIZE REPAIR WELL | | |
| PULL OR ALTER CASING | 片 H N_{GV} | (NOTE! Report results of multiple completion or zone change on Form 9–330.) |
| MULTIPLE COMPLETE | | |
| CHANGE ZONES | | |
| ABANDON* (other) | | |
| | | |
| including estimated da | ate of starting any proposed work. If well | state all pertinent details, and give pertinent dates, is directionally drilled, give subsurface locations and |
| measured and true ver | tical depths for all markers and zones per | tinent to this work.)* |
| | | |
| Plugged & Aband | oned Well As Follows: | |
| Pluq No. | Interval | Feet Sacks Cement |
| 1 | /D75 5005 | 150 |
| 2 | 6035-5885 4995-4845 | 150 75 150 75 |
| 3 | 2950-2800 | |
| 4 | 1300-1150 | 150 75 150 75 |
| 5 | 270-120 | 150 75 |
| 6 | 30-0 | 30 15 |
| Cleaned loostic | | |
| the location wi | n, renceu pits, and install | ed dry hole marker. When pits are dry |
| | | contour & reseeded to BLM Specifications |
| Subsurface Safety Valve: M. | anu. and Type | Set @ Ft. |
| | e foregoing is true and correct | |
| SIGNED AMABULINA | TITLE Drlg. & Prod. | Foreman DATE November 5, 1980 |
| H. D. HOL | NGSWORTH | |
| | (This space for Federal or Stat | te oπice use) |
| APPROVED BY | TITLE | |
| CONDITIONS OF APPROVAL, I | I DOLL | and the second of the second o |

*See Instructions on Reverse Side

MAY ± 0 1684 FARMS SAIGHT NEWS UNCE AREA

