

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well ☒ gas well ☐ other ☐

2. NAME OF OPERATOR
Aztec Energy Corporation

3. ADDRESS OF OPERATOR 87401
1206 E. 20th Street, Farmington, NM

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 2140' FSL, 990' FWL
AT TOP PROD. INTERVAL: 2140' FSL, 990' FWL
AT TOTAL DEPTH: 2140' FSL, 990' FWL

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:	SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF <input type="checkbox"/>	<input checked="" type="checkbox"/>
FRACTURE TREAT <input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE <input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL <input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE <input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES <input type="checkbox"/>	<input type="checkbox"/>
ABANDON* <input type="checkbox"/>	<input type="checkbox"/>
(other) <input type="checkbox"/>	<input type="checkbox"/>

5. LEASE NM 28741

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
LuLu

9. WELL NO.
#2

10. FIELD OR WILDCAT NAME
Lybrook Pool Extension

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 29, T.23N, R.6W

12. COUNTY OR PARISH 13. STATE
Sandoval New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
7106' GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spud well at 9:PM 8/16/82. Drilled a 12 1/4" hole to 275' KB. Ran 261' of 8 5/8" 24.0#/ft. casing and landed at 275' KB. Cemented with 200 sacks Class "B" containing 2% CaCl₂. Good circulation throughout job, cement circulated to surface. Plug down at 3:30 AM 8/17/82. WOC 12 hrs. Test casing and BOP at 1,000 psi - held OK.



Subsurface Safety Valve: Manu. and Type _____ @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Wayne R. Townsend TITLE VP of Operations DATE Augu 17, 1982

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY: