UNITED STATES DEPARTMENT OF THE INTERIOR **GEOLOGICAL SURVEY**

	SudBot parent 110: 45-165			
5. LEASE				
NM 28741			1.5	
6. IF INDIAN, ALL	OTTEE OR	RIBE	NAME	
	GUANT Mitologija		2 C	
7. UNIT AGREEM	ENT NAME	3		
		7		
8. FARM OR LEAS	ENAME		765	
Lu Lu			11 11 11	
9. WELL NO.			A 55	
•		12		

SUNDRY	NOTICES	AND	REPORTS	ON	WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.) gas other well well 2. NAME OF OPERATOR Aztec Energy Corporation 3. ADDRESS OF OPERATOR 1206 East 20th Street, Farmington, N.M. 87401 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 AT SURFACE: 2140' FSL, 990' FWL

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 29, T.23N, R.6W 328

10. FIELD OR WILDCAT NAME CALLED

Lybrook Peol Extension

AT TOP PROD. INTERVAL: 2140' FSL, 990' FWL 2140' FSL, 990' FWL AT TOTAL DEPTH:

12. COUNTY OR PARISH 13. STATE Sandoval New Mexico 14. API NO.

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

П

in or in 15. ELEVATIONS (SHOW DF, KDB AND WD) 7106' GR 0 10

change on 🕞 📆 🌣 330.)

Step boil

3

ting ting

Ž.

ibili

Figo.

9 d

Tego To Str Strine banisado

REQUEST FOR APPROVAL TO: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON* (other)

SUBSEQUENT REPORT OF: X (NOTE: Report results of multiple completion of zone U. S. SECLOSICAL BURYEY PARRATMOFUN, W. M.

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give still surface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled 7-7/8" hole to 5777', 8-24-82, Ran Dual Induction and Compensated Neutron Formation Density Logs. 8-25-82, Ran 5 - 14.0#/ft and 1555# 1555# The J-55 casing to 5777' with DV Tool at 4590'. Cemented first stage with 3 Class B Poxmix containing 12% gel and 10#/sk Gilsonite, 1060 60 ft. 35 Class B Poxmix with 6% gel and 10.0#/sk. Gilsonite and 59 god a character B Neat. Cement circulated to surface. Job eted 4:12 PM 8-25-82

Subsurface Safety Valve: Manu. and Type

bengi eldin mi tsin me are

7

18. I hereby certify that the foregoing is true and correct

TITLEV.P. Operations DATE August 26

(This space for Federal or State office use)

APPROVED BY CONDITIONS OF APPROVAL, IF ANY: TITLE .

SEP 0 3 1982

*See Instructions on Reverse Side

FARMINGTO: SWY BY.

3