and the free later is the

Form Approved. Budget Bureau No. 42-R1424

| UNITED STATES | 5. LEASE |
|---|--|
| DEPARTMENT OF THE INTERIOR | NM 28741 |
| GEOLOGICAL SURVEY | 6. IF INDIAN, ALLOTTEE OR TRIBE NAME |
| SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.) | 7. UNIT AGREEMENT NAME |
| reservoir, Use Form 9-331-C for such proposals.) | 8. FARM OR LEASE NAME |
| 1. oil gas | Lu Lu |
| well Well Cother | 9. WELL NO. |
| 2. NAME OF OPERATOR | 3 10. FIELD OR WILDCAT NAME |
| Aztec Energy Corporation | Lybrook Gallup Ext |
| 3. ADDRESS OF OPERATOR | 11. SEC., T., R., M., OR BLK. AND SURVEY OR |
| 1206 E. 20th St., Farmington, N.M. 87401 | AREA |
| 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 | Sec. 29, T23N, R6W |
| below.) AT SURFACE: 660' FSL & 2090' FWL | 12. COUNTY OR PARISH 13. STATE |
| at top prod. interval: Same | Sandoval New Mexico |
| AT TOTAL DEPTH: Same | 14. API NO. |
| 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, | |
| REPORT, OR OTHER DATA | 15. ELEVATIONS (SHOW DF, KDB, AND WD) |
| AUDOSOUSNIK DEDORT OF | 7255 Gr (7267 KDB) |
| REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: | - COSTAL CHI |
| TEST WATER SHUT-OFF FRACTURE TREAT RECEIVE | TO THE PARTY OF TH |
| SHOOT OR ACIDIZE | |
| PEPAIR WELL | (NOTE: Report results of multiple completion or zone |
| PULL OR ALTER CASING JUN 1 1983 | change on Form 9–330.) |
| MULTIPLE COMPLETE | |
| CHANGE ZONES | IRVEY. |
| (other) Surface casing and cemen FARMINGTON, N. I | M. |
| 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly statincluding estimated date of starting any proposed work. If well is a measured and true vertical depths for all markers and zones pertine | te all pertinent details, and give pertinent dates, directionally drilled, give subsurface locations and nt to this work.)* |
| Spud well @ 3:00PM. Dri Ran 6 joints (246') 8-2 casing. Set casing w/ 175 sacks (206.50 cu. 1 per sack and 2% CaCl ₂ . slurry to surface (11.2 7:45 PH, 5-27-83. WOC | Rig #5 moved on location. illed 12¼" mud hole to 261' KB 5/8", 2¼#, J55, STC, 8rd btm. @ 258' KB. Cemented w/ ft.) Class "B" w/ 1/¼# flocele Circulated 2 bbls. cement 22 cu. ft.). Plug down @ 12 hours. |
| May 28, 1983 Pressure test BOP and o | casing to 600 psig. Held ok. |
| Subsurface Safety Valve: Manu, and Type | Set @ Ft. |
| 18. I hereby certify that the foregoing is true and correct | 4 00 1002 |
| SIGNED Jemmono TITLE Agent | |
| R. D. Simmons (This space for Federal or State o | ffice use) [[UEFIEU FOR NEGORD] |
| | |
| APPROVED BY TITLE TITLE | - BATE - SAINLES SAGRE |
| | A 14 1111 A 14 1 A 17 1 A 186 76 |