

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

5. LEASE DESIGNATION AND SERIAL NO.

NM-19151

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

1.

OILWELL ☒ GAS WELL ☐ OTHER

7. UNIT AGREEMENT NAME

2. NAME OF OPERATOR Gary Williams Production Company

8. FARM OR LEASE NAME

San Isidro

3. ADDRESS OF OPERATOR 1775 Sherman St., Ste 1925

9. WELL NUMBER

Denver, CO 80202 (303) 831-4673

8

4. LOCATION OF WELL

AT SURFACE

10. FIELD AND POOL, OR WILDCAT

Rio Puerco - Mancos

1848' FNL, 732' FEL, Section 28-T20N-R3W

11. SEC., T., R., OR BLK. AND SURVEY

Section 28 - T20N - R3W

14. PERMIT NO.

15 ELEVATIONS

6752' KB

12. COUNTY OR PARISH

SANDOVAL

13. STATE

N.M.

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐ PULL OR ALTER CASING ☐

FRACTURE TREAT ☐ MULTIPLE COMPLETE ☐

SHOOT OR ACIDIZE ☐ ABANDON ☒

REPAIR WELL ☐ CHANGE PLANS ☐

OTHER ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐ REPAIR WELL ☐

FRACTURE TREATMENT ☐ ALTERING CASING ☐

SHOOTING OR ACIDIZING ☐ ABANDONMENT ☐

(OTHER)

☐

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS

Request approval to abandon well per the attached procedure.

RECEIVED  
OCT 26 1994  
OIL CON. DIV.  
DIST. 3

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Atty-in-Fact

DATE

2 May, 94

(This space for Federal or State office use)

APPROVED BY

Patricia M. Heister

Acting  
TITLE

Chief, Lands and Mineral Resources

DATE

OCT 20 1994

CONDITIONS OF APPROVAL, IF ANY:

NMOCD

**SAN ISIDRO #28-8**  
**Plug and Abandon Procedure**

SEE ATTACHED WELL DIAGRAM FOR TUBULAR DETAILS

1. Move in, rig up, service rig.
2. Pump tank bottoms into well.
3. Nipple up BOP's. Pick up tubing string and TIH to 3299'. Fill hole with gelled water.
4. TIH and set Class "H" cement plugs as follows: Plug #1, 25 sacks (30 cu. ft.) @ 3299' to 3199', Plug #2, 25 sacks (30 cu. ft.) from 617' to 500', Plug #3, 10 sacks (11.8 cu. ft.) from 50' to surface.
5. Cut off casing below ground level and erect dry hole marker.
6. Remove production equipment and reclaim location to BLM specifications.

March 31, 1994  
Charles H. Johns

Samuel Gary. Jr. & Associates  
 San Isidro 28-8 Wellbore Diagram  
 SENE Sec. 28 T20N R3W  
 Sandoval County. NM

Casing cemented w/ 300 sx 50/50  
 Pozmix and 100 sx Class G.

Ground ele. 6740'

13 1/2" hole

9 5/8", 36 lb/ft surface csg @ 617'

8 3/4" hole

7" Casing Breakdown

Interval	Weight	Grade	Conn.
0'-3299'	23	J-55	ST&C

Cemented with 410 sx 65/35 Pozmix and  
 100 sx Class Class B.

Cement circulated to surface

7" Casing at 3299'

6 1/4" Open Hole f/ 3299'-4050'

TD at 4050'