HNITED STATES

1. H 1 -3.1 Den 1. 23

CHIED SINIES					
DEPARTMENT	CF	THE	INTERIO	R	
GEOLOG	!CAL	SUF	RVEY		

UNITED STATES DEPARTMENT OF THE INTERIOR	5. LEASE		
GEOLOGICAL SURVEY	NM 14824 6. IF INDIAN, ALLOTTEE CR TRIBE NAME		
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different	7. UNIT AGREEMENT NAME		
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME		
1. oil K gas other	Ross Federal 12		
2. NAME OF OPERATOR	9. WELL NO. #27		
Cotton Petroleum Corporation	10. FIELD OR WILDÇAT NAME		
3. ADDRESS OF OPERATOR	Wildcat La		
3773 Cherry Creek Drive No, Denver, CO 80209 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREASection 27 T20N RIW NMPM		
below.) AT SURFACE: 400' FWL 1690' FNL Section 27	12. COUNTY OR PARISH 13. STATE		
AT TOP PROD. INTERVAL:	Sandoval New Mexico		
AT TOTAL DEPTH:	14. API NO.		
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA			
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD) 6967' GR		
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	0307 (1)		
TEST WATER SHUT-OFF			
SHOOT OR ACIDIZE			
PULL OR ALTER CASING	(NOTE: Report results of multiple completion or zone change on Form 9–330.)		
MULTIPLE COMPLETE			
CHANGE ZONES	er er 🛊		
ABANDON* (other) ABANDON* (other) ABANDON* ABANDON* ABANDON* ABANDON*	CONTROL ARCA		
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is d measured and true vertical depths for all markers and zones pertinen	irectionally drilled give subsurface locations and		
As per phone conversation w/Earl Beacher, Cot			
to D & A this well as follows:			
1. 25 sx plug at 2100-2000' (6-1/4" hole)			
 2. 25 sxs plug at 1890-1790' (6-1/4" hole) 3. Pull csg, cut off at 1650' +/- 			
4. 100' plug w/50' in and 50' out of 7" csg	stub		
5. 100' plug at 1100-1200'			
6. 100' plug at 9-5/8" csg shoe, 50' in and	50' out from 366-266'		
7. 10 sx plug at surface w/dry hole marker	duilling mud		
 Hole between plugs will be filled w/9.5# Reclaim location as per BLM specification 			

Subsurface Safety Valve: Manu. and 1	ype	Set @ F
18. I hereby certify that the foregoing	is true and correct	grAPPROVED, 1983
	(This space for Federal or State office use)	
APPROVED BY	TITLE (DEO 0 8 1983 COSTO AREA MANAGER/CIZCO SADAMAGOTON RESOURCE AREA /:

*See Instructions on Reverse Side

Daniel .