

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☐
well well other
2. NAME OF OPERATOR
Cotton Petroleum Corporation
3. ADDRESS OF OPERATOR
3773 Cherry Creek Drive No, Denver, CO 80209
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 400' FWL 1690' FNL Section 27
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

- ☐
☐
☐
☐
☐
☐
☐
☐
☒

RECEIVED

DEC 06 1983

BUREAU OF LAND MANAGEMENT
FARMINGTON DISTRICT OFFICE

5. LEASE
NM 14824
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
Ross Federal 12
9. WELL NO.
#27
10. FIELD OR WILDCAT NAME
Wildcat *Salley*
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Section 27 T20N R1W NMPM
12. COUNTY OR PARISH
Sandoval
13. STATE
New Mexico
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
6967' GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

This well was D & A'd as follows:

1. Load hole w/9.5 ppg drilling mud
2. Spot plug at 2100-2000'
3. Spot plug at 1890-1790'
4. Run free pt, cut off csg at 400', pull and LD 7" csg
5. Spot plug at 1200-1100'
6. Spot plug at 450-350', 50' in and 50' out of 7" csg
7. Plug 350' to surface in 9-5/8" csg, set dry hole marker.

RECEIVED

NOV 26 1984

OIL CON. DIV.

DIST. 3

FT.

Subsurface Safety Valve: Manu. and Type

18. I hereby certify that the foregoing is true and correct

SIGNED _____ TITLE Division Production Mgr. DATE November 29, 1983

(This space for Federal or State office use)

TITLE

APPROVED
AS AMENDED

Approved as to plugging of the well bore.
Liability under bond is retained until surface restoration is completed.

*See Instructions on Reverse Side

OCT 2 1984

/s/ J. Stan McKee

M. MILLENBACH
AREA MANAGER