

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

**SUNDRY NOTICES AND REPORTS ON WELLS**

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals

5. Lease Designation and Serial No.  
NM-84682,29169,84679

6. If Indian, Allottee or Tribe Name

**SUBMIT IN TRIPLICATE**

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

THE GARY-WILLIAMS COMPANY

3. Address and Telephone No.

1670 Broadway, Suite 3300, Denver, CO 80202 303-831-4673

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

460' FNL 125' FWL SEC 27-T21N-R3W  
D

7. If Unit or CA, Agreement Designation

Ceja Pelon

8. Well Name and No.

Ceja Pelon 27-4H #4

9. API Well No.

-043-30896

10. Field and Pool, or Exploratory Area

Undesignated Mancos

11. County or Parish, State

Sandoval County, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent  
☐ Subsequent Report  
☒ Final Abandonment Notice

TYPE OF ACTION

- ☒ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☐ Other

- ☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

1. Set CIBP at 3635'.
2. 30 SK cement plug 3635' to 3535'.
3. Perforate 2 noles @ 1575'.
4. Set cement retainer @ 1525'.
5. 54 SKS CL "B" cement. 24 SKS in formation. Filled casing from 1575' to 1475'
6. Perforate 2 holes @ 1150'.
7. Set cement retainer @ 1100'.
8. Could not pump into perforations.
9. Spotted 30 SKS CL "B" cement from 1100' to 1000'.
10. Perforate 2 holes @ 377'.
11. Pumped 54 SKS CL "B" cement. Displaced 24 SKS into formation. Remaining 30 SKS in casing from 377' to 277'.
12. Perforate 2 holes @ 50'.
13. Pumped 28 SKS CL "B" cement down casing.
14. Filled casing from 50' to surface with 28 SKS CL "B" cement. Cutoff wellhead.

14. I hereby certify that the foregoing is true and correct

Signed John A. Benton

Title Agent

Date 2/26/97

(This space for Federal or State office use)

Approved by Paul R. Stettin

Title for Chief, Lands and Mineral Resources

Date MAY 2 1997

Conditions of approval, if any:

Complete Surface Restoration

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.