

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐
2. NAME OF OPERATOR  
KENAI OIL AND GAS INC.
3. ADDRESS OF OPERATOR  
717 17th St., Ste. 2000, Denver, CO 80202
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE. 790' FNL - 1650' FWL  
AT TCP PROD. INTERVAL:  
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐ ☐

FRACTURE TREAT ☐ ☐

SHOOT OR ACIDIZE ☐ ☐

REPAIR WELL ☐ ☐

PULL OR ALTER CASING ☐ ☐

MULTIPLE COMPLETE ☐ ☐

CHANGE ZONES ☐ ☐

ABANDON\* ☐ ☐

(other) Casing ☐ ☒

5. LEASE  
N00-C-14-20-3743
6. IF INDIAN ALLOTTEE OR TRIBE NAME  
OR-91 N00-C-14-20-3743  
Navajo-Smiley Norberto
7. UNIT AGREEMENT NAME  
NONE
8. FARM OR LEASE NAME  
Union Navajo Allotted #5
9. WELL NO.  
#21
10. FIELD OR WILDCAT NAME  
Nageezi-Gallup
11. SEC. T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 5, T23N-R8W
12. COUNTY OR PARISH 13. STATE  
San Juan New Mexico
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
6975' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

3/17/80: TD 575'; Ran 14 jts., 8-5/8", 24#, J-8RT-STC-R3 casing to 573' KB and cemented to surface with 450 sxs. Class B cement with 3% CaCl and 1/4# Cello-Flake per sack. Cementing completed @ 6:45 p.m.

4/2/80: TD 6414'; Ran 153 jts. (6425.26'), 4-1/2", 10.5#, J-8RT-STC-R3 new casing with G.S., F.C. & DV tool (5.44') to 6414' with DV tool @ 5398' and cemented with 200 sacks, 50-50 Pozmix @ bottom and 650 sacks 50-50 Pozmix @ DV tool. See attached sheet for details.

Subsurface Safety Valve: Manu. and Type

Set @

18. I hereby certify that the foregoing is true and correct

SIGNED George B. Smith

Manager - Drilling and  
TITLE Production

DATE 6/3/80

(This space for Federal or State office use)

APPROVED BY  
CONDITION OF APPROVAL, IF ANY:

TITLE

DATE

JUN 18 1980

NMCCC

\* See instruction on Reverse Side

FARMINGTON DISTRICT  
BY George B. Smith



ACCEPTED FOR RECORD