

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☐ other ☐ Dry Hole  
2. NAME OF OPERATOR  
Champlin Petroleum Company  
3. ADDRESS OF OPERATOR  
P. O. Box 1257, Englewood, CO 80150  
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) NE SW  
AT SURFACE: 1726.7' FWL & 1855.1' FSL  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH: Same  
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:  
TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐

SUBSEQUENT REPORT OF:

☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☒

RECEIVED

OCT 14 1983

BUREAU OF LAND MANAGEMENT  
FARMINGTON RESOURCE AREA

5. LEASE N/M 36352  
6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
7. UNIT AGREEMENT NAME  
8. FARM OR LEASE NAME  
Pueblo Bonito Federal Unit #23-14  
9. WELL NO.  
1  
10. FIELD OR WILDCAT NAME  
Wildcat  
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 14-T22N-R10W  
12. COUNTY OR PARISH 13. STATE  
San Juan Utah/New Mexico  
14. API NO.  
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
6,306' GL, 321' KB

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Well was plugged and abandoned as follows:

Plug #1 5760-5660', 40 sx Type "B" cement  
Plug #2 4940-4840', 40 sx Type "B" cement  
Plug #3 4557-4457', 40 sx Type "B" cement  
Plug #4 3661-3561', 40 sx Type "B" cement  
Plug #5 1270-1170', 40 sx Type "B" cement  
Plug #6 564-350', 80 sx Type "B" cement  
50'-Surface, 20 sx Type "B" cement

Set dry hole marker & cleaned up location. Location will be reseeded with Seed Mixture 2 between July 1 and September 14, 1984 per BLM seeding requirements.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Ramona J. Rhoden TITLE Sr. Eng. Aide DATE NOV 10 1983

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE NOV 10 1984  
CONDITIONS OF APPROVAL, IF ANY:

Approved as to plugging of the well bore.  
Liability under bond is retained until  
surface restoration is completed.

NMOCC

M. MILLENDACH,  
AREA MANAGER