

5 BLM

1 Celsius-Denver

1 Celsius-SLC

1 BIA (Jerry Deppert)

1 File

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Budget Bureau No. 1004-0135
Expires August 31, 1985

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

5. LEASE DESIGNATION AND SERIAL NO.

N00-C-14-20-7307

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Navajo Allotted

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Bronze Medal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Undes. Gallup

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 3, T23N, R10W, NMPM

12. COUNTY OR PARISH

San Juan

13. STATE

NM

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

DUGAN PRODUCTION CORP.

3. ADDRESS OF OPERATOR

P O Box 208, Farmington, NM 87499

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

490' FNL - 970' FWL

RECEIVED

SEP 10 1985

BUREAU OF LAND MANAGEMENT
FARMINGTON RESOURCE AREA

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, ST, GR, etc.)

6688' GL; 6700' RKB

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

Spud & Surface Casing

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

M.I. & R.U. Four Corners Drilling Company rig #3. Spudded 12 1/4" hole at 12:15 PM on 9-8-85. Drilled to 220'. Ran 7 jts. 8-5/8" OD, 24#, J-55, 8 Rd, ST&C casing (T.E. 196.91') set at 210' RKB. Cemented with 135 sx class "B" plus 2% CaCl₂ (total cement slurry = 159 cf). Circulated approximately 1 1/2 bbls to surface. P.O.B. at 4:45 PM 9-8-85.

(Pressure tested B.O.P. & surface casing 600 psi for 30 minutes - held OK.)

RECEIVED

SEP 12 1985

OIL CON. DIV.
DIST. 3

18. I hereby certify that the foregoing is true and correct

SIGNED

Jim L. Jacobs

TITLE Geologist

DATE

9-9-85

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

*See Instructions on Reverse Side

NMOCC

FARMINGTON RESOURCE AREA
BY