1 File

Form	3160)_5	
(Nove	mper	r 1983)	•
(Form	erly	9-331	.)

UNITED STATES DEPARTMENT OF THE INTERIOR (Other Instructions on verse side)

SUBMIT IN TRIPLICATES

Form approved.	
Budget Bureau No.	1004-013
Expires August 31,	1985
	STAT MO

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

. L	EASS	DESIGN	MOITA	AND	BARL
NΜ	1 16	5762	_	/	

BUREAU OF	LAND	MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.

	(Do not use this form for proposal	ION FOR PERMIT-" for	r such proposals.)	
-			RECEIVED	A. UNIT AGREEMENT NAME
	WELL X WELL OTHER			8. FARM OR LEASE NAME
	NAME OF OPERATOR		UCT 11 19 8 5	Witty
	DUGAN PRODUCTION CORP.			9. WELL FO.
	ADDRESS OF OPERATOR	07400	BUREAU OF LAND MANAGEMENT	5
	P O Box 208, Farmington	, NM 8/499	rith any GAMMINGHOM RESOURCE AREA	10. FIELD AND POOL, OR WILDCAT
	See also apace it serems	arly and in accordance a		Undes. Gallup
	590' FNL - 860' FEL			11. SHC., T. R. M., OR BLK. AND SURVAY OR ARMA
				Sec.12,T23N,R10W,NMPM
		15. ELEVATIONS (Show w	hether DF, RT, CR, etc.)	12. COUNTY OR PARISH 13. STATE
4	PERMIT NO.	1	6854' RKB	San Juan NM

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data


		SUBSEQUENT EMPORT OF:	
NOTICE OF INTENTI	ON 10.		REPAIRING WELL
TEST WATER SHUT-OFF PC	LL OR ALTER CASING	WATER SHUT-OFF	ALTERING CASING
PRACTURE IREAL	ULTIPLE COMPLETE	SHOOTING OR ACIDIZING	ABANDONMENT®
SHOOT OF ACIDIZE	ANDON®	Spud & Surface	
REPAIR WELL	ANGE PLANS	(Note: Report results of a Completion or Recompletion	multiple completion on Well n Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and sones pertinent to this work.)*

M.I.& R.U. Four Corners Drilling Company rig #3. Spudded a 12½" hole at 10:15 AM 10-9-85. Drilled to 224'. Ran 7 joints 8-5/8" OD, 24#, 8 Rd ST&C casing (T.E. 206') set at 219' RKB.

Cemented with 135 sacks class "B" + 2% CaCl₂ (total cement slurry

159 cf). P.O.B. at 1:45 PM 10-9-85. Circulated approximately 2 bbls good cement to surface. Waited 12 hrs on cement. Tested BOP and surface casing 600 psi for 30 minutes before drilling out - held OK.



		·
8. I hereby certify that the foregoing is true and signed Jim L. Jacobs (This space for Federal or State office use). APPROVED BY CONDITIONS OF APPROVAL, IF ANY:	Geologist	10-10-85
	-	ACCEPTED FOR RECORD
	TITLE	007 18 1985
	HTT OCC	WARRIAGTON DECOUDED AREA

*See Instructions on Reverse Side FARMINGTON RESOURCE AREA