

Form 3160-5
November 1983)
Formerly 9-331)

6 BLM 1 File 1 BIA (Jerry Degroat)
UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

RECEIVED

DEC 02 1985

OIL WELL ☒ GAS WELL ☐ OTHER ☐

NAME OF OPERATOR

DUGAN PRODUCTION CORP.

ADDRESS OF OPERATOR

P O Box 208, Farmington, NM 87499 BUREAU OF LAND MANAGEMENT
FARMINGTON RESOURCE AREA

LOCATION OF WELL (Report location clearly and in accordance with BLM Form 1004-0135, Rev. 1-83.
See also space 17 below.)
At surface

1900' FN. - 2060' FEL

PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, OR, etc.)

6675' GL; 6687' RKB

5. LEASE DESIGNATION AND SERIAL NO.

N00-C-1420-5825

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Navajo Allotted

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Jim Thorpe

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Undes. Gallup

11. SEC., T., R., M., OR BLM, AND
SURVEY OR AREA

Sec. 3, T23N, R10W, NMPM

12. COUNTY OR PARISH 13. STATE

San Juan

NM

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

Spud & Surface Casing

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

7. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

Moved in & rigged up Four Corners Rig No. 3. Spudded 12 1/4" hole @ 8:45 PM 11-27-85. Drilled to 195'. Ran and cemented 7 jts. 8-5/8", 24#, J-55, 8 Rd, ST&C casing @ 194'. (T.E.=181.93'). Rigged up Cementers Inc and cemented surface casing with 135 sacks class "B" with 2% CaCl (slurry volume=159.3 cf). Circulated approximately 1 bbl of cement. Plug down @ 1:45 AM 11-28-85. Tested surface casing and BOP to 600 psi - held OK.

RECEIVED

DEC 04 1985

OIL CON. DIV.
DIST: 3

8. I hereby certify that the foregoing is true and correct

SIGNED

John D. Roe

TITLE

Petroleum Engineer

DATE

11-28-85

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

*See Instructions on Reverse Side

NMCCO

...and willfully make to any department or agency of the