	IN TRIPLICATE Expires August 31, 1985
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different use "APPLICATION FOR PERMIT—" for such proposals. RECE	t reservoir. Navajo Allotted 7. UNIT AGREEMENT NAME
OIL GAS OTHER	
NAME OF OPERATOR JAN 1	0 1986 8. FARM OR LEASE NAME
DUGAN PRODUCTION CORP.	Montreal
P O Box 208. Farmington NM 87499 BUREAU OF LAND FARMINGTON RE	D MANAGEMENT
LOCATION OF WELL (Report location clearly and in accordance with any State requiremen	ts. 10. FIELD AND POOL, OR WILDCAT
See also space 17 below.) At surface	South Bisti-Gallup
330' FNL - 2310' FWL	11. SHC., T., E., M., OR BLK. AND SURVEY OR ARMA
	Sec.4,T23N,R10W,NMPM
PERMIT NO. 15. BLEVATIONS (Show whether DF, RT, GR, etc.)	12. COUNTY OR PARISH 13. STATE
6608' GL; 6620' RKB	San Juan NM
Check Appropriate Box To Indicate Nature of Notice	ce, Report, or Other Data
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF PULL OR ALTER CASING WATER SE	HUT-OFF REPAIRING WALL
\\\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\	TREATMENT ALTERING CASING
SHOOT OR ACIDIZE ABANDON* SHOOTING	Spud & Surface Casing X
(Nor	rg: Report results of multiple completion on Well spletion or Recompletion Report and Log form.)
Moved in and rigged up Four Corne Spudded a 12½" hole @ 5:45 PM 1-6 6 jts. 8-5/8" OD, 24#, 8 Rd, ST&C RKB. Cemented with 135 sx class slurry 159 cf). P.O.B. @ 9:45 PM approx. 2 bbls.	-86. Drilled to 206'. Ran casing (T.E. 187.59') set @ 200' "B" plus 2% CaCl ₂ (total cement
Pressure tested BOP and surface c before drilling out - held OK.	asing to 600 psi for 30 minutes
•	
	$J_{A/J}$ $>_{0}$ \downarrow
	1028
	D.S. 3 214.)
I hereby certify that the foregoing is true and correct SIGNED TITLE Geologist	ACCEPTID8 F86 RECORD
SIGNED JIM Jacobs TITLE debigist	DATE
(This space for Federal or State office use)	JAN 17 1986
APPROVED BY TITLE	PATE
CONDITIONS OF APPROVAL, IF ANY:	1
	RV

*See Instructions on Reverse Side