

5 BLM 1 File
UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. <input checked="" type="checkbox"/> OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER		5. LEASE DESIGNATION AND SERIAL NO. NM 16762
2. NAME OF OPERATOR DUGAN PRODUCTION CORP.		6. IF INDIAN, ALLOTTEE OR TRIBE NAME
3. ADDRESS OF OPERATOR P O Box 208, Farmington, NM 87499		7. UNIT AGREEMENT NAME
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 2010' FSL - 1650' FWL		8. FARM OR LEASE NAME Witty
14. PERMIT NO.		9. WELL NO. 6
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 6763' GL; 6775' RKB		10. FIELD AND POOL, OR WILDCAT South Bisti-Gallup
BUREAU OF LAND MANAGEMENT FARMINGTON RESOURCE AREA		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 12, T23N, R10W, NMPM
		12. COUNTY OR PARISH San Juan
		13. STATE NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PCLL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

Spud & Surface Casing

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

M.I. & R.U. Four Corners Drilling Co. rig #8. Spudded a 12 $\frac{1}{4}$ " hole at 4:15 P.M. 3-23-87. Drilled to 205'. Ran 7 jts. 8-5/8" OD, 24#, 8 Rd., ST&C casing (T.E. 180.64') set @ 193' RKB. Cemented with 175 sx class "B" neat with 2% CaCl₂ (206.5 cf). Circulated 3 bbls cement to surface. P.O.B. @ 10:00 P.M. 3-23-87.

Pressure tested casing & BOP w/600 psi for 30 minutes before drilling out - held OK.

18. I hereby certify that the foregoing is true and correct

SIGNED

Jim L. Jacobs
Jim L. Jacobs

TITLE

Geologist

DATE

3-25-87

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

DATE

MAR 30 1987

FARMINGTON RESOURCE AREA

BY

*See Instructions on Reverse Side