

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

3. LEASE DESIGNATION AND SERIAL NO.

NOG-8505-1062

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Navajo Individual

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Louie Louie

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Bisti Gallup South

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 8, T23N, R9W, NMPM

12. COUNTY OR PARISH

San Juan

13. STATE

NM

1. OIL WELL ☒ GAS WELL ☐ OTHER

2. NAME OF OPERATOR
DUGAN PRODUCTION CORP.

3. ADDRESS OF OPERATOR
P O Box 208, Farmington, NM 87499

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface
2290' FSL - 710' FWL

BUREAU OF LAND MANAGEMENT
FARMINGTON RESOURCE AREA

14. PERMIT NO.

15. ELEVATIONS (Show whether DP, ST, GR, etc.)

6636' GL; 6648' RKB

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

REPAIR OR ALTER CASING

MULTIPLE COMPLETION

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

Spud & Surface Casing

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

X

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Moved in & rigged up Four Corners Drilling Co. rig #4. Spudded a 12 1/4" hole @ 11:00 AM 4-8-87. Drilled to 234'. Ran 5 jts. 8-5/8" OD, 24#, 8 Rd, ST&C casing (T.E. 209.25') set @ 221' RKB. Cemented with 135 sacks class "B" + 2% CaCl₂ (total cement slurry 159 cubic feet). Circulated 1 bbl cement to surface. P.O.B. 3:00 PM 4-8-87.

Pressure tested BOP & surface casing 600 psi for 30 minutes before drilling out - held OK.

18. I hereby certify that the foregoing is true and correct

SIGNED

Jim L. Jacobs

TITLE

Geologist

DATE

4-9-87

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

ACCEPTED FOR RECORD

DATE

APR 10 1987

FARMINGTON RESOURCE AREA

*See Instructions on Reverse Side