

5 BLM 1 File
UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

RECEIVED

APR 17 1987

3. LEASE DESIGNATION AND SERIAL NO.

NM 23744

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Olympic

9. WELL NO.

2

10. FIELD AND POOL, OR WILDCAT

South Bisti Gallup

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 3, T23N, R10W, NMPM

12. COUNTY OR PARISH

San Juan

13. STATE

NM

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, CR, etc.)

6695' GL; 6707' RKB

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Spud & Surface Casing

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

X

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Moved in & rigged up Four Corners Drilling Company rig #8.
Spudded a 12 $\frac{1}{4}$ " hole @ 10:45 AM 4-14-87. Drilled to 235'. Ran
5 jts. 8-5/8" OD, 24#, 8 Rd, ST&C casing (T.E. 210') set @ 222'
RKB. Cemented with 135 sacks class "B" plus 2% CaCl₂
(total cement slurry = 159 cf). Circulated 3 bbls cement to surface.
P.O.B. @ 2:00 PM 4-14-87. Pressure tested BOP and surface
casing before drilling out 600 psi for 30 minutes - held OK.

RECEIVED

APR 23 1987

OIL CON. DIV.
DIST. 3

18. I hereby certify that the foregoing is true and correct

SIGNED

Jim L. Jacobs

TITLE

Geologist

DATE

4-15-87

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

DATE

APR 23 1987

FARMINGTON RESOURCE AREA

*See Instructions on Reverse Side

BY