

5 BLM 1 File
UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved
Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

5. LEASE DESIGNATION AND SERIAL NO.

NM 32124

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Calgary

9. WELL NO.

88

10. FIELD AND POOL, OR WILDCAT

South Bisti Gallup

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 6, T23N, R10W, NMPM

12. COUNTY OR PARISH

San Juan

13. STATE

NM

RECEIVED

APR 28 1987

BUREAU OF LAND MANAGEMENT
FARMINGTON RESOURCE AREA

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, ST, CR, etc.)

6568' GL; 6580' RKB

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

Spud & Surface Casing

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

X

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Moved in & rigged up Four Corners Drilling Company rig #8.
Spudded a 12 $\frac{1}{4}$ " hole @ 4:30 PM 4-25-87. Drilled to 218'. Ran
5 jts. 9-5/8" OD, 43.50#, 8 Rd, LT&C casing (T.E. 193.87') set
@ 206' RKB. Cemented with 115 sacks class "B" plus 2% CaCl₂
(total cement slurry = 136 cf). P.O.B. @ 8:15 PM 4-25-87.
Circulated 2 bbls cement to surface.

(Pressure tested B.O.P. & surface casing 600 psi for 30 minutes
before drilling out - held OK.)

RECEIVED
APR 30 1987
OIL CON. DIV.
DIST. 3

18. I hereby certify that the foregoing is true and correct

SIGNED

Jim L. Jacobs

TITLE

Geologist

ACCEPTED FOR RECORD

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

DATE

APR 28 1987

FARMINGTON RESOURCE AREA

BY

SMW

*See Instructions on Reverse Side

NMOCC

Department or agency of the