Form 3160-5 (June 1990)

Final Abandonment Noti

UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

FORM AP	PROVED
Budget Bureau ?	Vo. 1004-0135
Expires: Mar	ch 31, 1993

	Expires:	March	31, E	793
Lease	Designat	ion and	Serie	l No.

. If Indian, Allottee or Tribe Name

Conversion to Injection

(Note: Report results of multiple completion on Well

☐ Dispose Water

NM 42059

	-	
form for proposals to drill or to deepen or reentry	y to a different reservoir.	ľ

Do not use this Use "APPLICATION FOR PERMIT—" for such proposals [10] (10)

SUNDRY NOTICES AND REPORTS ON WELLS

SUBMI	T IN TRIPLICATE	7. If Unit or CA, Agreement Designation
I. Type of Well Oil Well Other Other		8. Well Name and No.
2. Name of Operator		
Dugan Production Corp.		Champ #9
3. Address and Telephone No.		9. API Well No. 30 045 29287
P.O. Box 420, Farmington,	NM 87499 (505) 325-1821	10. Field and Pool, or Exploratory Area
4. Location of Well (Footage, Sec., T., R., M., or Survey [Description)	South Bisti Gallup
790' FSL & 1980' FEL (SW/4 S	SE/4)	11. County or Parish, State
Unit 0, Sec. 1, T23N, R10W		San Juan County, NM
12. CHECK APPROPRIATE BOX	s) TO INDICATE NATURE OF NOTICE, REP	
TYPE OF SUBMISSION	TYPE OF ACTIO	N
Notice of Intent DECE	Abandonment	Change of Plans
	Market 1 3 3 4	New Construction
LX Subsequent Report[]] MAR - 8	1993 Plugging Back	Non-Routine Fracturing
	1950 Casing Repair	Water Shut-Off

Completion or Recompletion Report and Log form.) 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Altering Casing

TD, casing & cement

T.D. 4980' reached on 3/3/96. TIH with 111 its. 43" 10.5# J-55 Newport casing landed at 4979', float collar at 4932', DV at 3807'. Cement 1st stage with 210 sx 50/50/2 with \# celloflake/sk (total cement slurry 1st stage = 267 cu.ft.). Cement pressure 650#. Displace with 20 bbls water, 59 mud. Plug down 1800 hrs 3/3/96. 1000# - held OK. Opened stage tool. Circulate 2% hours. Cement 2nd stage with 625 sx 65/35/12 with \(\frac{1}{2}\)# celloflake and tail with 150 sx 50/50/2 with \(\frac{1}{2}\) celloflake/sk (total cement slurry 2nd stage = 1572 cu.ft.). Total cement slurry both stages = 1839 cu.ft. Cement pressure 1150#. Displace with 61 bbls water. Plug down 2200 hrs 3/3/96. 2500# - held OK. Had good circulation throughout both stages. Circulated 20 bbls cement. Turbolizers @ 540' & 450'. Nipple down BOP, set slips & cut off casing. Rig released 2400 hrs 3/3/96.

(This space for Federal or State office use)	Title	Vice-President AC	CEPTED FOR RECORD
Approved by	Title		MAR 06 1996

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any sales Scientific diffraction statements or representations as to any matter within its jurisdiction.