

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE\*  
(Other instructions on reverse side)Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

Contract No. 39

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Jicarilla Apache

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

AXI Apache "C"

9. WELL NO.

2

10. FIELD AND POOL, OR WILDCAT

AXI Apache

11. SEC. T., R., M., OR BLM. AND  
SURVEY OR AREA

Sec. 34, T24N, R5W

12. COUNTY OR PARISH

Rio Arriba

13. STATE

New Mexico

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT" for such proposals.)1. OIL ☐ GAS ☒ WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Continental Oil Company

3. ADDRESS OF OPERATOR

152 North Durbin, Casper, Wyoming 82601

4. LOCATION OF WELL. Report location clearly and in accordance with any State requirements.  
See also space 17 below.  
At surface

990' FSL, 990' FEL New Mexico Unit Letter "PM"

14. PERMIT NO.

15. ELEVATIONS (Show whether of, RT, GR, etc.)

14. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETION

ABANDON\*

CHANGE PLANS

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

## SUBSEQUENT REPORT OF:

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

The well was drilled to a total depth of 2427' on October 29, 1955. 8 5/8" OD, 24# J-55 surface casing was set at 314' and cemented with 275 sacks of cement. 5 1/2" OD, 14#, J-55 production casing was set at 2425' and cemented with 275 sacks of cement.

AXI Apache "C" No. 2 was disconnected from the pipeline in late 1968. This well was marginal on completion. No remedial possibilities exist and deepening the well to the Mesa Verde is uneconomical due to the 5 1/2" casing; therefore, we are submitting this notice of intention to abandon this well.

We are proposing to plug and abandon Well No. 2 by placing a 40 sack cement plug across the perforations from 2310' to 2340' and on top of the Pictured Cliffs formation. The second plug will cover the Ojo Alamo from 2100' to 1800'. The 5 1/2" OD casing will be cut and pulled at approximately 314' RBM and a third cement plug will be placed across the cut off point and into the 8 5/8" surface casing. The last plug will be the surface plug inside the 8 5/8" surface casing. Heavy drilling mud will be placed between each of the four plugs and a regulation P&A marker will be installed. The location will be cleaned up and restored to its natural condition.

USGS(4) NMOCC(2) EXXON Co.(1) File(2)

18. I hereby certify that the foregoing is true and correct

SIGNED

*J. A. W. W. W.*

TITLE Administrative Supervisor

DATE 3-14-73

(This space for Federal or State office use)

APPROVED BY  
CONDITIONS OF APPROVAL, IF ANY

APR 6 1973

A. F. WILLIBRAND  
ACTING DISTRICT ENGINEER

TITLE

DATE

APR 5 1973

\*See Instructions on Reverse Side

U. S. GEOLOGICAL SURVEY  
DENVER, COLO.