

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.
5. LEASE DESIGNATION AND SERIAL NO.
Santa Fe #070909

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐	7. UNIT AGREEMENT NAME *****
2. NAME OF OPERATOR Mobil Oil Company	8. FARM OR LEASE NAME Ingramson Fed.
3. ADDRESS OF OPERATOR 10737 So. Shoemaker Avenue, Santa Fe Springs, California	9. WELL NO. 1
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 660 feet North of the South line and 660 feet West of the East line of Section 20.	10. FIELD AND POOL, OR WILDCAT Lindrieth Dakota
14. PERMIT NO. *****	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 20, T24N, R21W, N40W
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 7176' Ground	12. COUNTY OR PARISH Rio Arriba
	13. STATE New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐	WATER SHUT-OFF ☐	REPAIRING WELL ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETE ☐	FRACTURE TREATMENT ☐	ALTERING CASING ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☒	SHOOTING OR ACIDIZING ☐	ABANDONMENT* ☐
REPAIR WELL ☐	CHANGE PLANS ☐	(Other) ☐	

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)


17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Due to high operating and maintenance costs with very little production this well has been temporarily abandoned since 1959. Mobil requests to abandon the well as follows:

1. All perforations to be plugged with cement.
2. Intervals between any cement plugs to be covered with 10.0 ppg mud.
3. If 7" casing recovered below the 9-5/8" casing shoe @ 4732', both the 7" stub and the 9-5/8" casing shoe are to be plugged with minimum of 50 linear feet of cement both in and out of the casing. Depending upon the depth of recovery, this would mean either one or two plugs.
 - a) If 7" casing is recovered above 4732', a minimum plug of 50 linear feet, both in and out of the stub, is required.
4. A surface cement plug, plate, and 4" iron pipe abandonment marker, all of which conform to USGS and NMCC requirements are to be placed.

All cement plugs including surface plugs are to be placed with tubing.

Work to begin on or about March 29, 1965.



18. I hereby certify that the foregoing is true and correct

SIGNED James M. Bumbach TITLE District Engineer DATE March 22, 1965

(This space for Federal or State office use)

APPROVED BY JM TITLE _____
CONDITIONS OF APPROVAL, IF ANY:

Dist: USGS-6
Fm.-1
File-1

*See Instructions on Reverse Side

RECEIVED

DATE

MAR 24 1965

U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.