Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

5. Lease Designation and Serial No.

SF-0	78924-A	
JE-U	/ U J L 4 – A ·	

SUNDRY NOTICES AND REPORTS ON WELLS


Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.

Use "APPLICATION FOR PERMIT—" for such proposals

6. If Indian, Allottee or Tribe Name

SUBMI	T IN TRIPLICATE	7. If Unit or CA, Agreement Designation
I. Type of Well Oil Well Well Other		Escrito Gallup
2. Name of Operator		8. Well Name and No.
		#18 (formerly 3-21 #1)
BCO, INC.		9. API Well No.
3. Address and Telephone No.		30-03905423 -
135 Grant, Santa Fe, NM 8750		10. Field and Pool, or Exploratory Area
4. Location of Weil (Footage, Sec., T., R., M., or Survey I	Description)	Escrito Gallup
790 FNL - 1650 FWL S21 T24N, R7W NMPM		
	,	11. County or Parish, State
		Rio Arriba, NM
12. CHECK APPROPRIATE BOX	(s) TO INDICATE NATURE OF NOTICE, REPO	RT, OR OTHER DATA
TYPE OF SUBMISSION	TYPE OF ACTION	
Notice of Intent	Abandonment	Change of Plans
	Recompletion	New Construction
Subsequent Report	Plugging Back	Non-Routine Fracturing
	Casing Repair	Water Shut-Off
Final Abandonment Notice	Altering Casing	
	X Other surface restoration	Conversion to Injection
į.	& reseeding	_ L Dispose Water
13 D	_	(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)
give subsurface locations and measured and true verti	all pertinent details, and give pertinent dates, including estimated date of starting cal depths for all markers and zones pertinent to this work.)*	any proposed work. If well is directionally drilled.

The surface restoration has been completed. The reseeding was completed on September 10, 1993. The contractor who did the reseeding was Robert E. Ramirez of Cuba, New Mexico.



14. I hereby certify that the foregoing is true and correct			ACCEPTED
Signed James & Bener	Title	Office Manager	ACCEPTED FOR RECORD
(This space for Federal or State office use)			NOV - 8 1993
Approved by Conditions of approval, if any:	Title		FARMINGTON DISTRICT OFFICE
			.^

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR



FORM APPROVED Bugget Bureau No. 1004-0135 Expires: March 31, 1993

BUREAU OF	LAND MANAGEMENT	SF-078924-A
Do not use this form for proposals to dr	AND REPORTS ON WELLS ill or to deepen or reentry to a different reservoir. R PERMIT—" for such proposals	6. If Indian, Allottee or Tribe Name
SUBMIT	IN TRIPLICATE	7. If Unit or CA, Agreement Designation Escrito Gallup
Oil Gas Well Other		8. Well Name and No. #18
2. Name of Operator BCO, TNC.		Formerly (3-21,#1) 9. API Well No.
3 Address and Telephone No.		3003905423
135 Grant Avenue	Santa Fe, NM 87501 escription) 7263'61	10. Field and Pool, or Exploratory Area
4. Location of Well (Footage, Sec., 1., R., M., or Survey D	FWL 7263 GL	Escrito Gallup 11. County or Parish, State
521,T24N,R7		Rio Arriba
2. CHECK APPROPRIATE BOX	s) TO INDICATE NATURE OF NOTICE, REPO	RT, OR OTHER DATA
TYPE OF SUBMISSION	TYPE OF ACTION	
Notice of Intent	Abandonment	Change of Plans
Subsequent Report	Recompletion Plugging Back	New Construction Non-Routine Fracturing
	Casing Repair	Water Shut-Off
Final Abandonment Notice	Altering Casing	Conversion to Injection
	Other	Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)
13. Describe Proposed or Completed Operations (Clearly state a	ll pertinent details, and give pertinent dates, including estimated date of startin cal depths for all markers and zones pertinent to this work.)*	
The Plug and	d abandonment was c	completed
Attachments:	on Detailed Report of Op	RECEIVED BLM
		Z = 0
		N

Approved as to plugging of the well bore. Liability under bond is retained until surface restoration is complete:

I. I hereby certify that the soragoing is true and correct Signed	Title Senior Field Engineer	Date 07/24/35
(This space for Federal or State office use) Approved by	Title	APPROVED
Conditions of approval, if any:		AUG 09 1993

ESCRITO GALLUP UNIT NUMBER 18 (FORMERLY 3-21 #1) DETAILED REPORT OF OPERATIONS

7-19-93 A-PLUS WELL SERVICE MOVED RIG AND CEMENTING EQUIPMENT TO THE NANCY NUMBER.

7-20-93
RIGGED UP RIG AND CEMENTING EQUIPMENT, NIPPLED DOWN WELL HEAD AND NIPPLED
UP BOP. UNSEATED TUBING DONUT AND TRIPPED OUT OF THE HOLE WITH 193 JOINTS
OF 2 3/8" EUE TUBING. TRIPPED IN HOLE TO 5987' AND MIXED AND PUMPED 35 SX
OF CLASS "B" CEMENT LEAVING CEMENT FROM 5987' TO 5526'. TRIPPED TUBING UP
OUT OF THE CEMENT AND SHUT DOWN FOR THE DAY.

7-21-93 DROVE TO LOCATION AND OPENED WELL. TRIPPED IN HOLE AND TAGGED THE TOP OF CEMENT AT 5522', MIXED AND SPOTTED 23 BARRELS OF 8.4 PPG, 40 VIS GELLED MUD FROM 5500' TO 4158'. LAID DOWN TUBING TO 4218', MIXED AND PUMPED 13 SX OF CLASS "B" CEMENT, LEAVING CEMENT FROM 4218' TO 4044'. PULLED UP OUT OF CEMENT AND MIXED AND SPOTTED 22 BARRELS OF 8.4 PPG, 40 VIS GELLED MUD FROM 3900' TO 2546'. LAID DOWN TUBING TO 2605'. MIXED AND PUMPED 24 SX OF CLASS "B" CEMENT, LEAVING CEMENT FROM 2605' TO 2289'. PULLED UP OUT OF CEMENT AND MIXED AND SPOTTED 5 BARRELS OF 8.4 PPG, 40 VIS GELLED MUD FROM 2100' TO 1870'. LAID DOWN TUBING TO 1861', TRIPPED TUBING OUT OF THE HOLE. RIGGED UP TO PERFORATE AND PERFORATED 4, .5" HOLES AT 1920'. TRIPPED IN HOLE WITH 4 1/2" DOWNHOLE SERVICES CEMENT RETAINER AND SET AT 1861'. PRESSURE TESTED TUBING TO 1500 PSIG AND ESTABLISHED AN INJECTION RATE OF 800 PSIG AT 1.5 BARRELS PER MINUTE. MIXED AND PUMPED 75 SX OF CLASS "B" CEMENT, PUMPED 70 SX UNDER RETAINER, STUNG OUT OF RETAINER AND PUMPED 5 SX OF CEMENT ON TOP OF RETAINER. PULLED UP, MIXED AND PUMPED 23 BARRELS OF 8.4 PPG, 40 VIS GELLED MUD FROM 1700' TO 262'. LAID DOWN ALL OF THE TUBING AND RIGGED UP TO PERFORATE AND PERFORATED 2, .5" HOLES AT 262'. RIGGED DOWN PERFORATORS. ESTABLISHED CIRCULATION DOWN CASING AND UP AND OUT THE BRAIDEN HEAD.

7-22-93
DROVE TO LOCATION AND OPENED WELL UP. MIXED AND PUMPED 118 SX OF CLASS
"B" CEMENT, LEAVING CEMENT FROM 262' TO SURFACE. NIPPLED DOWN BOP, CUT
WELL HEAD OFF AND INSTALLED DRY HOLE MARKER. RIGGED DOWN RIG AND
CEMENTING EQUIPMENT AND MOVED OFF OF LOCATION.
AS SOON AS PRACTICAL BUT NO LATER THAN ONE YEAR AFTER THE COMPLETION OF
THIS PLUG AND ABANDONMENT, BCO, INC. SHALL RESTORE THE LOCATION TO A SAFE
AND CLEAN CONDITION.