


Form 9-331a  
(Feb. 1961)



(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Land Office Santa Fe

Lease No. 88-011895

Unit \_\_\_\_\_

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL		REPORT OF SETTING <u>5 1/2"</u> CASING	<u>XX</u>

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Astec, New Mexico October 9, 19 57

Well No. 1 is located 1490 ft. from S line and 1850 ft. from E line of sec. 14

SE 1/4 Sec. 14 94N 6W N.M.P.M.  
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)  
Otero Pk Rio Arriba New Mexico  
(Field) (County or Subdivision) (State or Territory)

The elevation of the Ground above sea level is 6506 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

CASING DETAILS:

Run 55 Jts., 2279.90', J-8 5 1/2" OD 14 1/2 casing with Baker float shoe and collar, 3 centralizers 10', 30', and 110' off bottom. Welded bottom 3 collars solid. Landed depth, 2275' KB.

Cemented with 35 sac regular, 35 cu. ft. stratacrete, 6 1/2 gal. WOC at 5: 35 A.M.

Tested casing to 1000 psi. Test OK.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company PURCO PETROLEUM CORPORATION

Address 106 West Cimaha

Astec, New Mexico

By H. L. Sealing

Title Dist. Engr.