

Form 7-231  
(May 1963)UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE\*  
(Other instructions on reverse side)Form Approved  
Publications No. 40-11424

5. LEASE DESIGNATION AND AREA NO.

NY-03595-A

6. IF INDIAN, RESERVE OR TRIBE NAME

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different formation.  
Use "APPLICATION FOR PERMIT" for such proposals.)

1.

OIL WELL ☒ GAS WELL ☐ OTHER

2. NAME OF OPERATOR

BCO, Inc.

3. ADDRESS OF OPERATOR

135 Grant Ave. Santa Fe, New Mexico 87501

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface

1980 FSL 1980 FEL 17-24N-7W NMPM

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, CR, etc.)

GL 7296

7. UNIT ACCESSION NAME

Escrito

8. FARM OR LEASE NAME

Escrito Unit

9. WELL NO.

13

10. FIELD AND TOWN, OR WILDCAT

Escrito Gallup

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

17-24N-7W NMPM

12. COUNTRY OR PROVINCE 13. STATE

Rio Arriba NM

(Coleen #1)

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

XX

PULL OR ALTER CASING


MULTIPLE COMPLETION

ABANDON\*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF


FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT


(Note: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting or proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and append to this work).\*

4-20-82 Set BP at 5850. Determined there was a hole in the casing. Notified Richard Bell with Minerals Management at 3:00 P.M. of casing hole and that we intended to cement at 7:30 A.M. on 4-21-82.

Determined hole between 230 and 245 (KB). Injection rate 1/4 bbl. at 1000#'s. Blows down from 500# to 0# in 2 minutes.

4-21-82 Obtained verbal approval from Richard Bell to perforate 2 shots at 260 (KB) and cement thru casing failure and perf's at 260 with 150 sacks Class H cement, 4# salt and 2% Ca Cl. Cement job to be at approximately 11:00 A.M. today 4-21-82.

It is hoped we will be able to circulate cement to the surface, but procedure should meet current USGS plugging requirements of putting plug on backside from 50' below surface pipe to 50' above surface shoe.



18. I hereby certify that the foregoing is true and correct

SIGNED

APPROVED

TITLE President

DATE 4-21-82

(This space for Federal or State Office Use)

APR 23 1982

APPROVED BY  
CONDITIONS OFJAMES F. SIMS  
DISTRICT ENGINEER

TITLE

NMOCCA

DATE

