


(SUBMIT IN TRIPLICATE)

Indian Agency Jicarilla Tribal

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Allottee Jicarilla "C"

Lease No. Contract #34



SUNDRY NOTICES AND REPORTS ON WELLS

| | | |
|---|--|-------------------|
| NOTICE OF INTENTION TO DRILL | SUBSEQUENT REPORT OF WATER SHUT-OFF | <u>Production</u> |
| NOTICE OF INTENTION TO CHANGE PLANS | SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING | |
| NOTICE OF INTENTION TO TEST WATER SHUT-OFF | SUBSEQUENT REPORT OF ALTERING CASING | |
| NOTICE OF INTENTION TO REDRILL OR REPAIR WELL | SUBSEQUENT REPORT OF REDRILLING OR REPAIR | <u>FEB 2 1959</u> |
| NOTICE OF INTENTION TO SHOOT OR ACIDIZE | SUBSEQUENT REPORT OF ABANDONMENT | |
| NOTICE OF INTENTION TO PULL OR ALTER CASING | SUPPLEMENTARY WELL HISTORY | |
| NOTICE OF INTENTION TO ABANDON WELL | <u>Report of Perforations</u> | |
| | <u>Report of Sand/Oil Fracing</u> | <u>X</u> |

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

January 30, 1959

Jicarilla "C"
Well No. 22 is located 1980 ft. from N line and 440 ft. from E line of sec. 33

SE 1/4 - NE 1/4 Section 33
(1/4 Sec. and Sec. No.)

25N
(Twp.)

9W
(Range)

N.M.P.M.
(Meridian)

Otero (Gallup)
(Field)

Rio Arriba
(County or Subdivision)

New Mexico
(State or Territory)

The elevation of the derrick floor above sea level is 6793 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudlogging jobs, cementing points, and all other important proposed work)

Ran & set $5\frac{1}{2}$ " casing at 6291' w/Halliburton DV tool at 3926'. Cemented 1st stage around shoe w/125 sks. reg. cement & 114 sks. strata crite, 45 gal. Temperature survey on 1st stage indicated top of cement behind $5\frac{1}{2}$ " casing at 3270'. Cemented 2nd stage thru DV tool at 3926' w/500 sks. reg. cement, 25 gal. Temperature survey indicated top of cement behind $5\frac{1}{2}$ " casing at 2090'.

Perforated $5\frac{1}{2}$ " casing w/4 McCullough bullets per ft. as follows: 6142-98', 6182-96', 6206-28' & 6242-52', total 56', 224 bullets.

Frased Gallup formation, down $5\frac{1}{2}$ " casing & 2" tubing, thru $5\frac{1}{2}$ " casing perfor. 6142-98', 6182-96', 6206-28' & 6242-52' w/25,000# 20/40 sand & 25,200 gals. of lvs. oil by Dowell. SWP 2700#, Max. IP 2700#, Min. IP 2400#, Inj. rate 24 BPM. Standing pressure 1900#.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company SKELLY OIL COMPANY

Address Box 426
Farmington, New Mexico

By (Signed) P. E. COOPER

Title District Superintendent