


(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Indian Agency Jicarilla Tribal
Allottee Jicarilla "B"
Lease No. Contract # 68
Tract # 127



SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF REDRILLING OR REPAIR.....
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....
NOTICE OF INTENTION TO ABANDON WELL.....	<u>Report of perforations</u>
	<u>Report of Sand-Oil frac</u>

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Jicarilla "B"

March 9, 1960

Well No. 21 is located 790 ft. from N line and 790 ft. from W line of sec. 32

NW/4 - Section 32
(1/4 Sec. and Sec. No.)

25N
(Twp.)

5N
(Range)

NMPN
(Meridian)

Dakota - Otero Ext.
(Field)

Rio Arriba
(County or Subdivision)

New Mexico
(State or Territory)

The elevation of the derrick floor above sea level is 6734 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Perforated 5-1/2" OD casing with 4 Land-Wells "E" gun bullets per foot in the Dakota formation as follows:

6999' - 7004'	(5')	20 holes
7032' - 7058'	(26')	104 holes
7064' - 7072'	(8')	32 holes
TOTAL	(39')	156 holes

Ran 2" EUE tubing and set at 7045' with 3' perforated nipple and pin collar on bottom. Sand-Oil treated down Casing and tubing, through above listed perforations, with 840 barrels of crude oil and 20,000# of 40-60 sand. Flushed with 160 barrels of crude oil. Formation broke from 3200# to 2800#. Maximum treating pressure 3700#. Minimum treating pressure 3300#. Shut down pressure 3700#. Injection rate 17 BPM. Standing pressure 1425# in 2 hours.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company SKELLY OIL COMPANY
Box 426

Address Farmington, New Mexico

By (Signed) P. E. Gosper

Title District Superintendent